



# Cisco Catalyst 9200/9200L Series Switches 17.12

## CC Configuration Guide

**Version:** 0.7

**Date:** July 16, 2024

## Table of Contents

1.	Introduction.....	7
1.1.	Audience .....	7
1.2.	Purpose.....	7
1.3.	Document References.....	7
1.4.	TOE Overview.....	8
1.5.	Operational Environment .....	8
1.6.	Excluded Functionality.....	8
2.	TOE Acceptance.....	10
3.	Procedures and Operational Guidance for IT Environment.....	11
4.	Preparative Procedures and Operational Guidance for the TOE.....	11
4.1.	Switch — Power Up.....	11
4.2.	Switch — Initial Configuration.....	11
4.2.1.	Configure Time and Date.....	12
4.2.2.	Enable Configuration Change Notification and Logging.....	13
4.2.3.	Configure Local Logging Buffer Size .....	14
4.2.4.	Generate Logs on Failed Login Attempts .....	14
4.2.5.	Include Date on Audit Records.....	14
4.2.6.	Generate Logs on Successful Login Attempts .....	14
4.2.7.	Set Syslog Server Logging Level .....	14
4.2.8.	Enable Debug Logging.....	14
4.2.9.	Configure Required Logging.....	15
4.2.10.	Configure Local Authentication.....	15
4.2.11.	Configure Authentication Failure.....	15
4.2.12.	Define Password Policy .....	15
4.2.13.	Add Administrator Account .....	16
4.2.14.	Session Termination.....	17
4.2.15.	Access Banner.....	17

Introduction

- 4.2.16. Verify TOE Software ..... 18
- 4.2.17. SSH Remote Administration Protocol ..... 18
- 4.2.18. Disable Unused Protocols..... 21
- 4.2.19. IPsec..... 21
- 4.2.19.1. Generating a Crypto Key Pair for IPsec..... 22
- 4.2.19.2. Create Trustpoints for IPsec ..... 22
- 4.2.19.3. IKEv2..... 24
- 4.2.19.4. IPsec Transform Sets and SA Lifetimes..... 25
- 4.2.19.5. IPsec Crypto Map and Access Control List..... 26
- 4.2.19.6. Security Policy Database (SPD) ..... 27
- 4.2.19.7. Configure Reference Identifier ..... 28
- 4.2.19.8. IKEv2 Fragmentation ..... 28
- 4.2.19.9. Enable Remote Syslog Server..... 28
- 4.2.20. MACSEC and MKA Configuration ..... 29
- 4.2.21. Protect CAK Data ..... 30
- 4.2.22. FIPS Mode ..... 30
- 4.2.23. Verify FIPS Mode ..... 31
- 5. Operational Guidance for the TOE ..... 31
  - 5.1. Access CLI Over SSH ..... 31
  - 5.2. View Audit Events ..... 31
  - 5.3. Unblock Locked-Out Account..... 31
  - 5.4. Cryptographic Self-Tests ..... 31
  - 5.5. Zeroize Private Key ..... 31
  - 5.6. MACsec Session Interruption and Recovery..... 32
  - 5.7. IPsec Session Interruption and Recovery ..... 32
  - 5.8. Update TOE Software ..... 32
    - 5.8.1. One-Shot Upgrade ..... 32
    - 5.8.2. Multi-Stage Upgrade..... 33
- 6. Auditing ..... 34

Introduction

7.	Obtaining Documentation and Submitting a Service Request.....	48
8.	Contacting Cisco .....	48

**Prepared By:**

Cisco Systems, Inc.  
170 West Tasman Dr.  
San Jose, CA 95134

This document provides Guidance to IT personnel for the TOE, Cisco Catalyst 9200/9200L Series Switches 17.12. This Guidance document includes instructions to successfully install the TOE in the Operational Environment, instructions to manage the security of the TSF, and instructions to provide a protected administrative capability.

**Revision History**

Version	Date	Change
0.1	October 4, 2023	Initial Version
0.2	October 12, 2023	Updates to revert to IPsec
0.3	November 27, 2023	Updates to add CSfC requirements
0.4	March 14, 2024	Updates to address CCTL comments
0.5	April 4, 2024	Updates to Address Check-in Comments
0.6	July 1, 2024	Updates to Address Check-Out Comments
0.7	July 16, 2024	Updates to Address Check-Out Comments

## Introduction

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

© 2024 Cisco Systems, Inc. All rights reserved.

# 1. Introduction

This Operational User Guidance with Preparative Procedures documents the administration of the Cisco Catalyst 9200/9200L Series Switches 17.12 TOE, as it was certified under Common Criteria. The TOE may be referenced below as the Cat 9K Switches, TOE, or Switch.

## 1.1. Audience

This document is written for administrators installing and configuring the TOE. This document assumes that you are familiar with the basic concepts and terminologies used in internetworking, and understand your network topology and the protocols that the devices in your network can use, that you are a trusted individual, and that you are trained to use the operating systems on which you are running your network.

## 1.2. Purpose

This document is the Operational User Guidance with Preparative Procedures for the Common Criteria evaluation. It was written to highlight the specific TOE configuration and administrator functions and interfaces that are necessary to configure and maintain the TOE in the evaluated configuration. This document is not meant to detail specific actions performed by the administrator but rather is a road map for identifying the appropriate locations within Cisco documentation to get the specific details for configuring and maintaining switch operations. All security relevant commands to manage the TSF data are provided within this documentation within each functional section.

## 1.3. Document References

This section lists the Cisco Systems documentation that is also a portion of the Common Criteria Configuration Item (CI) List. The documents used are shown below in Table 1. Throughout this document, the guides will be referred to by the “#”, such as [1].

**Table 1 Cisco Documentation**

#	Title	Link
1	Release Notes for Cisco Catalyst 9200 Series Switches, Cisco IOS-XE Dublin 17.12.x	<a href="https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/software/release/17-12/release_notes/ol-17-12-9200.html">https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/software/release/17-12/release_notes/ol-17-12-9200.html</a>
2	Cisco Catalyst 9200 Switches Hardware Installation Guide)	<a href="https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/hardware/install/b-c9200-hig.html">https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/hardware/install/b-c9200-hig.html</a>
3	Software Configuration Guide, Cisco IOS-XE Dublin 17.12.x (Catalyst 9200 Switches)	<a href="https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/software/release/17-12/configuration_guide/b-1712-9200-cg.html">https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/software/release/17-12/configuration_guide/b-1712-9200-cg.html</a>
4	Security Configuration Guide, Cisco IOS XE Dublin 17.12.x (Catalyst 9200 Switches)	<a href="https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/software/release/17-12/configuration_guide/sec/b_1712_sec_9200_cg/configuring_authorization.html">https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst9200/software/release/17-12/configuration_guide/sec/b_1712_sec_9200_cg/configuring_authorization.html</a>
5	Command Reference, Cisco IOS-XE Dublin 17.12.x (Catalyst 9200 Switches)	<a href="https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/prog/command/1712/b_1712_programmability_cr.html">https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/prog/command/1712/b_1712_programmability_cr.html</a>
6	Cisco IOS Configuration Fundamentals Command Reference	<a href="https://www.cisco.com/c/en/us/td/docs/ios/fundamentals/command/reference/cf_book.html">https://www.cisco.com/c/en/us/td/docs/ios/fundamentals/command/reference/cf_book.html</a>
7	System Message Guide for Cisco IOS XE Dublin 17.12.x	<a href="https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/17_xe/syslogs/17-12-x/b-system-message-guide-17-12-x.html">https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/17_xe/syslogs/17-12-x/b-system-message-guide-17-12-x.html</a>

#	Title	Link
8	Troubleshoot MACSEC on Catalyst 9000	<a href="https://www.cisco.com/c/en/us/support/docs/switches/catalyst-9300-series-switches/216849-troubleshoot-macsec-on-catalyst-9000.html">https://www.cisco.com/c/en/us/support/docs/switches/catalyst-9300-series-switches/216849-troubleshoot-macsec-on-catalyst-9000.html</a>

## 1.4. TOE Overview

The Cisco Catalyst 9200/9200L Series Switches 17.12 TOE is an enterprise access-layer switch for branch office deployments. Switches are used to connect multiple devices, such as computers, wireless access points, printers, and servers; on the same network within a building or campus. A switch enables connected devices to share information and talk to each other and are key building blocks for any network.

## 1.5. Operational Environment

The TOE requires the following IT Environment Components when the TOE is configured in its evaluated configuration:

**Table 2. Operational Environment Components**

Component	Usage/Purpose Description
Audit (syslog) Server	This includes any syslog server to which the TOE transmits syslog messages over IPsec.
Local Console	This includes any IT Environment Console that is directly connected to the TOE via the Serial Console Port and is used by the TOE administrator to support TOE administration. This interface is accessible and available locally even if the network were to go down.
Management Workstation with Secure Shell v2 (SSHv2) client	This includes any IT Environment Management workstation that is used by the TOE administrator to support TOE administration using SSHv2 protected channels. Any SSH client that supports SSHv2 may be used.
Media Access Control security (MACsec) Peer	This includes any MACsec peer with which the TOE participates in MACsec communications. MACsec Peer may be any device that supports MACsec communications.

## 1.6. Excluded Functionality

The functionality listed below is not included in the evaluated configuration.

**Table 3. Excluded Functionality and Rationale**

Function Excluded	Rationale
Non-FIPS 140-2 mode of operation	The TOE includes FIPS mode of operation. The FIPS modes allows the TOE to use only approved cryptography. FIPS mode of operation must be enabled in order for the TOE to be operating in its evaluated configuration.
HTTP/HTTPS	Remote Management is performed using SSH



Introduction

SNMP	Remote Management is performed using SSH
------	--

Additionally, the TOE includes a number of functions where there are no Security Functional Requirements that apply from the collaborative Protection Profile for Network Devices v2.2 or the PP-Module for MACsec Ethernet Encryption v1.0. The excluded functionality does not affect the TOE's conformance to the claimed Protection Profiles.

**Warning:** Use of other cryptographic engines beyond what is required for the TOE was not evaluated nor tested during the CC evaluation.

## 2. TOE Acceptance

The administrator should perform the following actions to ensure the TOE is correct and that it has not been tampered with during delivery.

1. Before unpacking the TOE, inspect the physical packaging the equipment was delivered in. Verify that the external cardboard packing is printed with the Cisco Systems logo and motifs. If it is not, contact the supplier of the equipment (Cisco Systems or an authorized Cisco distributor/partner).
2. Verify that the packaging has not obviously been opened and resealed by examining the tape that seals the package. If the package appears to have been resealed, contact the supplier of the equipment (Cisco Systems or an authorized Cisco distributor/partner).
3. Verify that the box has a white tamper-resistant, tamper-evident Cisco Systems bar coded label applied to the external cardboard box. If it does not, contact the supplier of the equipment (Cisco Systems or an authorized Cisco distributor/partner). This label will include the Cisco product number, serial number, and other information regarding the contents of the box.
4. Note the serial number of the TOE on the shipping documentation. The serial number displayed on the white label affixed to the outer box will be that of the device. Verify the serial number on the shipping documentation matches the serial number on the separately mailed invoice for the equipment. If it does not, contact the supplier of the equipment (Cisco Systems or an authorized Cisco distributor/partner).
5. Verify that the box was indeed shipped from the expected supplier of the equipment (Cisco Systems or an authorized Cisco distributor/partner). This can be done by verifying with the supplier that they shipped the box with the courier company that delivered the box and that the consignment note number for the shipment matches that used on the delivery. Also verify that the serial numbers of the items shipped match the serial numbers of the items delivered. This verification should be performed by some mechanism that was not involved in the actual equipment delivery, for example, phone/FAX or other online tracking service.
6. Once the TOE is unpacked, inspect the unit. Verify that the serial number displayed on the unit itself matches the serial number on the shipping documentation and the invoice. If it does not, contact the supplier of the equipment (Cisco Systems or an authorized Cisco distributor/partner).

### 3. Procedures and Operational Guidance for IT Environment

To operate in its evaluated configuration, the TOE requires the operational components listed in Table 2. Below are additional details needed to configure the Syslog server:

- Syslog Server. Any syslog server that can be accessed over IPsec may be used. Install the syslog server per installation instructions provided with the syslog server software.

### 4. Preparative Procedures and Operational Guidance for the TOE

To operate in its evaluated configuration, the TOE requires the operational components listed in Table 2. Below are additional details needed to configure the Syslog server:

#### 4.1. Switch — Power Up

**Warning: IMPORTANT SAFETY INSTRUCTIONS**

**Blank faceplates and cover panels serve three important functions: they prevent exposure to hazardous voltages and currents inside the chassis; they contain electromagnetic interference (EMI) that might disrupt other equipment; and they direct the flow of cooling air through the chassis. Do not operate the system unless all cards, faceplates, front covers, and rear covers are in place.**

1. If you are powering up the switch, move the power switch to the ON position. Listen for the fans; you should immediately hear them operating. Ensure that the power supply LED OK is green and the FAIL LED is not illuminated. The front-panel indicator LEDs provide power, activity, and status information useful during bootup. For more detailed information about the LEDs, see the LEDs section in the Hardware Installation Guide.
2. Observe the initialization process. When the system boot is complete (the process takes a few seconds), the Switch begins to initialize.

Loading from ROMMON with a System Image in Bootflash

3. When initialization has completed, the following will be displayed:

Press RETURN to get started!

#### 4.2. Switch — Initial Configuration

1. The administrator will be prompted to enter the initial configuration dialog. Enter no and confirm you would like to terminate autoinstall. The CC Configuration will use manual steps to provide the initial configuration.

```
Would you like to enter the initial configuration dialog? [yes/no]: no
```

```
Would you like to terminate autoinstall? [yes];yes
```

```
Press RETURN to get started!
```

2. Enter privilege EXEC mode

```
SWITCH> enable
```

3. Enter configure terminal

```
SWITCH# configure terminal
```

4. Configure a hostname

```
SWITCH(config)# hostname mySWITCH
```

5. Configure the Enable Secret Password using Type 9

```
SWITCH(config)# enable algorithm-type scrypt secret <the unencrypted (cleartext) 'enable' secret>
```

**Note:** Compose a password with a length between 8 and 16 using any combination of upper and lower case letters, numbers, and the following special characters: “!”, “@”, “#”, “\$”, “%”, “^”, “&”, “\*”, “(”, “)”

6. Configure Gigabit Ethernet Management Interface VRF

```
Enter: SWITCH(config)# do show running-config vrf
```

If there was not a Mgmt-vrf automatically created follow the steps below to create one:

```
SWITCH(config)# vrf definition Mgmt-vrf
```

```
SWITCH(config-vrf)# address-family ipv4
```

```
SWITCH(config-vrf)# exit-address-family
```

```
SWITCH(config-vrf)# address-family ipv6
```

```
SWITCH(config-vrf)# exit-address-family
```

```
SWITCH(config-vrf)# exit
```

7. Provide an initial configuration for the Management Interface. For example:

```
SWITCH(config)# interface GigabitEthernet0/0
```

```
SWITCH(config-if)# ip address <IP address> <mask>
```

```
SWITCH(config-if)# vrf forwarding Mgmt-vrf
```

```
SWITCH(config-if)# no shutdown
```

```
SWITCH(config-if)# exit
```

8. Configure a default route to reach the Switch and a default route for the Mgmt-vrf

```
SWITCH(config)# ip route <prefix> <mask> <default gateway/next hop>
```

```
SWITCH(config)# ip route vrf Mgmt-vrf <prefix> <mask> <default gateway/next hop>
```

9. Configure the console to require username and password authentication

```
SWITCH(config)# line console 0
```

```
SWITCH(config-line)# login authentication default
```

10. Save the initial configuration to nvram by executing “wr mem” or “copy system:running-config nvram:startup-config” command.

### 4.2.1. Configure Time and Date

Perform the following to configure time and date.

1. Enter enable and then enter configuration mode.

```
SWITCH> enable
```

```
SWITCH# configure terminal
```

2. Configure the time zone. The zone argument is the name of the time zone (typically a standard acronym). The hours-offset argument is the number of hours the time zone is different from UTC. The minutes-offset argument is the number of minutes the time zone is different from UTC. For example clock timezone EST -5

```
SWITCH(config)# clock timezone zone-hours-offset [minutes-offset]
```

3. [Optional] Configure daylight savings time in areas where it starts and ends on a particular day of the week each year. The offset argument is used to indicate the number of minutes to add to the clock during summer time. For example clock summer-time PST recurring 1 monday january 12:12 4 Tuesday december 12:12 120

```
SWITCH(config)# clock summer-time zone recurring [week day month hh : mm week day month hh : mm [offset]]
```

4. [Optional] Configure a specific summer time start and end date. The offset argument is used to indicate the number of minutes to add to the clock during summer time. For example clock summer-time PST date 1 january 1999 12:12 4 december 2001 12:12 120

```
SWITCH(config)# clock summer-time zone date month year hh:mm date month year hh : mm [offset]1:5
```

5. Configure Calendar time as authoritative.

```
SWITCH(config)# clock calendar-valid
```

6. Return to privileged EXEC mode.

```
SWITCH(config)# end
```

7. Set the clock using the clock set command. For example clock set 12:12:12 1 january 2011

```
SWITCH# clock set hh : mm : ss date month year
```

## 4.2.2. Enable Configuration Change Notification and Logging

The Configuration Change Notification and Logging feature tracks changes made to the Cisco software running configuration. Perform the following steps to ensure all required audit events are logged.

1. Ensure logging is enabled

```
SWITCH(config)# logging on
```

2. Enter archive config mode

```
SWITCH(config)# archive
```

3. Enter logging config sub-mode

```
SWITCH(config-archive)# log config
```

4. Enable the config logger

```
SWITCH(config-archive-log-cfg)# logging enable
```

5. Suppress password when displaying logged commands

```
SWITCH(config-archive-log-cfg)# hidekeys
```

6. Enter the number of entries to be retained. The range is from 1 to 1000; the default is 100

```
SWITCH(config-archive-log-cfg)# logging size <1-1000>
```

7. Enable sending of logged commands to remote syslog server

```
SWITCH(config-archive-log-cfg)# notify syslog
```

8. Exit configuration mode and return to privileged EXEC mode

```
SWITCH(config-archive-log-cfg)# end
```

### 4.2.3. Configure Local Logging Buffer Size

Configure the size of the local logging buffer. The local logging buffer size can be configured in a range of <4096-2147483647> bytes.

**Note:** It is recommended to not make the buffer size too large because the TOE could run out of memory for other tasks. It is recommended to set it to at least 150000000

```
SWITCH(config)# logging buffer 150000000
```

If the local storage space for audit data is full the TOE will overwrite the oldest audit record to make room for the new audit record.

### 4.2.4. Generate Logs on Failed Login Attempts

To generate logs for failed login attempts enter

```
SWITCH(config)# login on-failure log
```

### 4.2.5. Include Date on Audit Records

To include the year with the time stamp on all audit records in the message log enter:

```
SWITCH(config)# service timestamps log datetime year
```

### 4.2.6. Generate Logs on Successful Login Attempts

To generate logs for successful login attempts enter

```
SWITCH(config)# login on-success log
```

### 4.2.7. Set Syslog Server Logging Level

Set syslog server logging level to debug

```
SWITCH(config)# logging trap debugging
```

### 4.2.8. Enable Debug Logging

To generate all required audit events, the following debug commands must be entered each time the TOE is restarted:

```
SWITCH# debug crypto pki validation
```

```
SWITCH# debug crypto pki transaction
```

```
SWITCH# debug crypto pki api
```

```
SWITCH# debug crypto pki messages
```

```
SWITCH# debug crypto isakmp
```

```
SWITCH# debug crypto ipsec
```

```
SWITCH# debug crypto ikev2
```

```
SWITCH# debug crypto engine
```

**Warning:** If the Administrator restarts the TOE the debug commands above must be re-entered.

## 4.2.9. Configure Required Logging

To generate additional required audit events, the following commands must be configured:

```
SWITCH(config)# ip ssh logging events
SWITCH(config)# crypto logging session
SWITCH(config)# crypto logging ikev2
```

## 4.2.10. Configure Local Authentication

1. To enable the authentication, authorization, and accounting (AAA) access control model, issue the `aaa new-model` command in global configuration mode.

```
SWITCH(config)# aaa new-model
```

2. To set the default authentication at login to use local authentication use the `aaa authentication login default local` command

```
SWITCH(config)# aaa authentication login default local
```

3. To set the default authorization method to use local credentials use the `aaa authorization exec default local` command

```
SWITCH(config)# aaa authorization exec default local
```

## 4.2.11. Configure Authentication Failure

To block brute-force attack attempts, the Switch needs to be configured for authentication failure. The administrator needs to define the maximum number of failed login attempts within a time period. In addition, the administrator needs to define the time period to ban an offending account.

1. Specify the value for maximum number of failed attempts within a time period (seconds), and the time period (seconds) to ban an offending account.

```
SWITCH(config)# aaa authentication rejected <1-25> in <1-65535> ban <1-65535>
```

For example, to block accounts for 10 minutes after 5 failed login attempts within one 1 hour, enter:

```
aaa authentication rejected 5 in 3600 ban 600
```

2. Exit configuration mode and return to privileged EXEC mode

```
SWITCH(config)# end
```

## 4.2.12. Define Password Policy

Administrators must define a “`aaa common-criteria policy`” and apply the policy to each local account. This ensures password changes will prompt for your old password before allowing a new password and will also ensure passwords contain a minimum of 8 characters.

1. Create the AAA security password policy and enter common criteria configuration policy mode.

```
SWITCH(config)# aaa common-criteria policy <policy name>
```

2. Set the minimum length for passwords. The TOE supports a minimum length from 1 to 127 characters. It’s recommended to configure a minimum length between 8 and 16 characters:

```
SWITCH(config-cc-policy)# min-length <8-16>
```

3. Set a password lifetime appropriate for your organization. For example, to set a password lifetime of 90 days enter:

```
SWITCH(config-cc-policy)# lifetime day 90
```

When the password expires the user will be prompted to perform a password change.

4. Type exit to return to the main configuration mode.

```
SWITCH(config-cc-policy)# exit
```

5. To verify the Common Criteria password policy enter

```
SWITCH(config)# do show aaa common-criteria policy <policy name>
```

### 4.2.13. Add Administrator Account

The administrator should create and use a new account that has the Common Criteria Password Policy applied. To add an administrative account use the username command in configuration mode. You will need to specify the Common Criteria Password Policy.

```
SWITCH(config)# username <user> privilege 15 common-criteria-policy <policy name> algorithm-type <scrypt> secret password <the unencrypted (cleartext) password for the user>
```

Passwords may be composed of any combination of upper- and lower-case letters, numbers, and the following special characters:

**Table 4. Password Special Characters**

Special Character	Name
!	Exclamation
@	At sign
#	Number sign (hash)
\$	Dollar sign
%	Percent
^	Caret
&	Ampersand
*	Asterisk
(	Left parenthesis
)	Right parenthesis
	Space
;	Semicolon
:	Colon
"	Double Quote
'	Single Quote



	Vertical Bar
+	Plus
-	Minus
=	Equal Sign
.	Period
,	Comma
/	Slash
\	Backslash
<	Less Than
>	Greater Than
_	Underscore
`	Grave accent (backtick)
~	Tilde
{	Left Brace
}	Right Brace

#### 4.2.14. Session Termination

All sessions at the local console and auxiliary port must terminate after an Administrator specified time interval of session inactivity has elapsed. Use the steps below to configure the time interval.

1. Enter the line configuration mode for console.

```
SWITCH(config)# line console 0
```

2. Specify the timeout value in minutes. The range is from 0 to 35791.

```
SWITCH(config-line)# exec-timeout <time in minutes>
```

3. Enter the line configuration mode for aux port:

```
SWITCH(config-line)# line aux 0
```

4. Specify the timeout value in minutes. The range is from 0 to 35791.

```
SWITCH(config-line)# exec-timeout <time in minutes>
```

#### 4.2.15. Access Banner

The administrator should configure an initial banner that describes restrictions of use, legal agreements, or any other appropriate information to which users consent by accessing the Switch. The banner will display on the CLI and SSH interface prior to allowing any administrative access.

To configure an access banner, follow the steps below

1. In privilege EXEC mode, enter configure terminal

```
SWITCH# config terminal
```

2. Enter the banner text using 'banner login delimiter message delimiter' format. Do not use " or % as a delimiting character. White space characters will not work.

```
SWITCH(config)# banner login z <message text> z
```

Message text. The text is alphanumeric, case sensitive, and can contain special characters. It cannot contain the delimiter character you have chosen. The text has a maximum length of 80 characters and a maximum of 40 lines.

To clear a login banner use "no login banner"

## 4.2.16. Verify TOE Software

The pre-installed image shipped with the TOE may not be the CC validated version of **cat9k\_lite\_iosxe.17.12.03.SPA.bin**. Follow the steps below to verify if you have the CC validated version.

1. Enter show version and verify the version is 17.12

```
SWITCH# show version | include Software
```

2. If the version is not 17.12 you will need to obtain the 17.12 software image. Navigate to Cisco Software Central at <https://software.cisco.com>. Use your Cisco Care Online (CCO) or SMART account and download the 17.12 image.
3. To update the software, refer to section 4.8 of the this document.

## 4.2.17. SSH Remote Administration Protocol

The TOE provides remote administration using SSH. The steps below provide instructions to configure SSH Server for the CC evaluated configuration. For additional information on SSH refer to the "Configuring Secure Shell" Chapter of [4]. If you downloaded the entire contents of [4] in PDF format the "Configuring Secure Shell" is in Chapter 13.

1. In privileged EXEC mode, enter configure terminal

```
SWITCH# configure terminal
```

2. Specify the host domain name applicable to the Switch

```
SWITCH(config)# ip domain name cisco.com
```

3. Generate a crypto key for SSH. Assign a label such as SSH-KEY

```
SWITCH(config)# crypto key generate rsa label SSH-KEY modulus [2048 | 3072]
```

**Note:** CNSS customers that require conformance to Commercial Solutions for Classified Program (CSfC) program, the modulus size for the RSA key will need to be 3072.

4. Assign the key pair to SSH

```
SWITCH(config)# ip ssh rsa keypair-name SSH-KEY
```

5. Enable SSHv2. This will also deny use of SSHv1

```
SWITCH(config)# ip ssh version 2
```

6. Configure the SSH Server Key Exchange

```
SWITCH(config)# ip ssh server algorithm kex ecdh-sha2-nistp256 ecdh-sha2-nistp384
```

7. Specify the allowed encryption algorithms and the order they are to be supported

```
SWITCH(config)# ip ssh server algorithm encryption aes256-gcm@openssh.com aes128-gcm@openssh.com
aes256-cbc aes128-cbc
```

**Note:** CNS customers that require conformance to Commercial Solutions for Classified Program (CSfC) program the encryption algorithm must be at least one of: `aes256-gcm@openssh.com` and/or `aes256-cbc`

8. Specify the allowed Message Authentication Code (MAC) algorithms and the order they are to be supported

```
SWITCH(config)# ip ssh server algorithm mac hmac-sha2-256
```

**Note:** When (and only when) the encryption algorithm selected in step 7 above is `aes256-gcm@openssh.com` or `aes128-gcm@openssh.com` supplying the MAC algorithm is skipped. When `aes128-gcm@openssh.com` or `aes256-gcm@openssh.com` is used as the encryption algorithm, the MAC algorithm is implicit.

9. The administrator needs to configure the Switch for SSH public key authentication. This is necessary to avoid a potential situation where password failures by remote Administrators lead to no Administrator access for a temporary period of time. During the defined lockout period, the Switch provides the ability for the Administrator account to login remotely using SSH public key authentication.

Before proceeding, please have the SSH public key ready for use. The public key is generated from your SSH client on the Management workstation.

- a. Configure Public Key Algorithms for SSH public-key based authentication

```
SWITCH(config)# ip ssh server algorithm publickey ssh-rsa
```

- b. Configure Host Key Algorithms for SSH public-key based authentication

```
SWITCH(config)# ip ssh server algorithm hostkey rsa-sha2-256 rsa-sha2-512
```

- c. Enter public-key configuration mode

```
SWITCH(config)# ip ssh pubkey-chain
```

- d. Specify the admin user account to configure for SSH public key authentication

```
SWITCH(conf-ssh-pubkey-user)# username admin
```

- e. Enter public-key data configuration mode

```
SWITCH(conf-ssh-pubkey-user)# key-string
```

- f. Paste the data portion of the public key generated from the SSH client. **Note:** If necessary you may split the key into multiple lines.

```
SWITCH(conf-ssh-pubkey-data)# <paste your public key>
```

- g. Return to configuration mode by entering exit 3 times:

```
SWITCH(conf-ssh-pubkey-data)# exit
```

```
SWITCH(conf-ssh-pubkey-user)# exit
```

```
SWITCH(conf-ssh-pubkey)# exit
```

10. SSH connections with the same session keys cannot be used longer than one hour, and with no more than one gigabyte of transmitted data. In the steps below configure a time-based and volume-based (in kilobytes) rekey values. **Note:** Values can be configured to be lower if desired. The minimum time value is 10 minutes. The minimum volume value is 100 kilobytes.

**Note:** To ensure rekeying is performed before one hour expires, the Administrator should specify a rekey time of 59 minutes:

```
SWITCH(config)# ip ssh rekey time 59
```

```
SWITCH(config)# ip ssh rekey volume 1000000
```

11. Display SSH configuration information

```
SWITCH(config)# do show ip ssh
```

12. Confirm the SSH configuration includes the following settings. Your choice for encryption and MAC algorithms may be a subset of this list.

- SSH Enabled - version 2.0
- Authentication methods: publickey or password
- Authentication Publickey Algorithms: ssh-rsa
- Hostkey Algorithms: rsa-sha2-256, rsa-sha2-512
- Encryption Algorithms: aes256-gcm@openssh.com, [aes128-gcm@openssh.com](https://openssh.com), aes256-cbc, aes128-cbc
- MAC Algorithms: hmac-sha2-256
- KEX Algorithms: ecdh-sha2-nistp256,ecdh-sha2-nistp384

13. Enter line configuration mode to configure the virtual terminal line settings 0 4

```
SWITCH(config)# line vty 0 4
```

14. Specify vty lines 0-4 to use only SSH

```
SWITCH(config-line)# transport input ssh
```

15. Specify a timeout value for vty lines 0-4

```
SWITCH(config-line)# exec-timeout <time in minutes>
```

16. Type Exit

```
SWITCH(config-line)# exit
```

17. Enter line configuration mode to configure the virtual terminal lines 5-15

```
SWITCH(config)# line vty 5 15
```

18. Specify the vty lines to use only SSH

```
SWITCH(config-line)# transport input ssh
```

19. Specify a timeout value for vty lines 5-15

```
SWITCH(config-line)# exec-timeout <time in minutes>
```

20. Exit configuration mode and return to privileged EXEC mode

```
SWITCH(config)# end
```

21. Enter "show running-config" and verify all vty lines include "transport input SSH" and have a configured timeout value

```
SWITCH# show running-config
```

**Note:** RSA signature services using 2048 or 3072 key sizes are automatically configured when SSH is configured as instructed in the steps above.

Before proceeding to the next section, logout out of your local console CLI session by entering either “exit or “logout”

The remaining preparative procedures can be performed using the local console or remotely over SSH.

## 4.2.18. Disable Unused Protocols

The following remote management protocols (HTTP, HTTPS, SNMP) were not tested in the evaluated configuration and must be disabled:

```
SWITCH(config)# no ip http server
```

```
SWITCH(config)# no ip http secure-server
```

```
SWITCH(config)# no snmp-server
```

## 4.2.19. IPsec

IPsec is a framework of open standards developed by the IETF. It provides security for the transmission of sensitive information over unprotected networks such as the Internet. IPsec acts at the network layer, protecting and authenticating IP packets between participating IPsec device(s). In the CC evaluated configuration IPsec is required to provide protected transmission of audit events to remote syslog server. This protection is provided with a syslog server operating as an IPsec peer of the TOE and the records tunneled over that connection.

The Administrator defines which packets are considered sensitive and should be sent through these secure tunnels and specifies the parameters that should be used to protect these sensitive packets by specifying the characteristics of these tunnels. When the IPsec recognizes a sensitive packet, the Switch sets up the appropriate secure tunnel and sends the packet through the tunnel to the remote peer.

More accurately, these tunnels are sets of security associations (SAs) that are established between two IPsec peers. The SAs define the protocols and algorithms to be applied to sensitive packets and specify the keying material to be used by the two peers. SAs are unidirectional and are established per the ESP security protocol.

The administrator defines the traffic that needs to be protected between two IPsec peers by configuring access lists and applying these access lists to interfaces using crypto map sets. Therefore, traffic may be selected on the basis of the source and destination address, and optionally the Layer 4 protocol and port. (The access lists used for IPsec are only used to determine the traffic that needs to be protected by IPsec, not the traffic that should be blocked or permitted through the interface. Separate access lists define blocking and permitting at the interface.)

A crypto map set can contain multiple entries, each with a different access list. The crypto map entries are searched in a sequence and the Switch attempts to match the packet to the access list specified in that entry. When a packet matches a permit entry in a particular access list, and the corresponding crypto map entry is tagged, IPsec is triggered. If there is no SA that IPsec can use to protect this traffic to the peer, IPsec uses IKE to negotiate with the remote peer to set up the necessary IPsec SAs on behalf of the data flow. The negotiation uses information specified in the crypto map entry as well as the data flow information from the specific access list entry.

Once established, the set of SAs (outbound to the peer) is then applied to the triggering packet and to subsequent applicable packets as those packets exit the Switch. "Applicable" packets are packets that match the same access list criteria that the original packet matched. For example, all applicable packets could be encrypted before being forwarded to the remote peer. The corresponding inbound SAs are used when processing the incoming traffic from that peer.

Access lists associated with IPsec crypto map entries also represent the traffic that the Switch needs protected by IPsec. Inbound traffic is processed against crypto map entries. If an unprotected packet matches a permit entry in a particular access list associated with an IPsec crypto map entry, that packet is dropped because it was not sent as an IPsec-protected packet.

Crypto map entries also include transform sets. A transform set is an acceptable combination of security protocols, algorithms, and other settings that can be applied to IPsec-protected traffic. During the IPsec SA negotiation, the peers agree to use a particular transform set when protecting a particular data flow.

### 4.2.19.1. Generating a Crypto Key Pair for IPsec

1. In privileged EXEC mode, enter configure terminal

```
SWITCH# configure terminal
```

2. The Administrator can choose to generate an elliptic curve or RSA key. Assign a label such as IPSEC-KEY

```
SWITCH(config)# crypto key generate rsa general modulus <2048 | 3072> label IPSEC-KEY
```

**Note:** CNSS customers that require conformance to Commercial Solutions for Classified Program (CSfC) program the modulus size for the RSA key will need to be 3072.

### 4.2.19.2. Create Trustpoints for IPsec

IPsec must be configured to use X.509v3 certificates supporting a minimum path length of three (root CA -> intermediate CA -> end-entity). Therefore, you will need to create two trustpoints. The section below provides steps to create a root CA and a subordinate CA using CA certificates from your organization's PKI. Before proceeding, please have the root CA and subordinate CA certificates ready for import from your CA administrator.

**Note:** You will set up the CRL certificate revocation mechanism used to ensure that the certificate of the IPsec peer has not been revoked. If the TOE is unable to obtain a CRL, the TOE will reject the peer's certificate and a "CRL fetch for trustpoint <trustpoint name> failed" message will appear in the message log (refer to section 6 for details on audit). The Administrator will need to enable the remote syslog server and/or remote login authentication as described below in sections 4.2.21.10 and 4.2.21.11, respectively, once the revocation server is back online.

**Note:** The TOE uses X.509v3 certificates to support authentication for IPsec connections. The TSF determines the validity of certificates by ensuring that the certificate and the certificate path are valid in accordance with RFC 5280. The certificate path is validated by ensuring that all the CA certificates have the basicConstraints extension and the CA flag is set to TRUE and the certificate path must terminate with a trusted CA certificate. OCSP is not supported; therefore the OCSP Signing purpose (id-kp 9 with OID 1.3.6.1.5.5.7.3.9) is trivially satisfied by the TOE. Revocation checking is performed on the leaf and intermediate certificate(s) when authenticating a certificate chain provided by the remote peer.

1. Create, configure, and authenticate a root trustpoint for IPsec

```
SWITCH(config)# crypto pki trustpoint <root trustpoint name>
```

```
SWITCH(ca-trustpoint)# enrollment terminal pem
```

```
SWITCH(ca-trustpoint)# revocation-check none
```

```
SWITCH(ca-trustpoint)# chain-validation stop
```

```
SWITCH(ca-trustpoint)# crypto pki authenticate <root trustpoint name>
```

Enter your base 64 encoded root CA certificate. End with a blank line or the word "quit" on a line by itself. When prompted enter yes to accept the CA certificate. The Switch should respond with:

```
"Trustpoint CA certificate accepted."
```

```
"% Certificate successfully imported"
```

2. Create, configure, and authenticate the subordinate trustpoint:

```
SWITCH(config)# crypto pki trustpoint <subordinate trustpoint name>
```

```
SWITCH(ca-trustpoint)# enrollment terminal pem
```

```
SWITCH(ca-trustpoint)# revocation-check none
```

```
SWITCH(ca-trustpoint)# chain-validation continue <root trustpoint name>
```

```
SWITCH(ca-trustpoint)# subject-name C=<two letter country code>, ST=<two letter state code>, L=<locality>,  
O=<organization>, OU=<organizational unit>, CN=Switch
```

```
SWITCH(ca-trustpoint)# rsakeypair IPSEC-KEY
```

Authenticate the trustpoint

```
SWITCH(ca-trustpoint)# crypto pki authenticate <subordinate trustpoint name>
```

Enter your base 64 encoded subordinate CA certificate. End with a blank line or the word "quit" on a line by itself. When prompted enter yes to accept the CA certificate. The Switch should respond with:

```
"Trustpoint CA certificate accepted."
```

```
"% Certificate successfully imported"
```

3. Generate a certificate signing request for the Switch

```
SWITCH(config)# crypto pki enroll <subordinate trustpoint name>
```

When prompted to include the router serial number and IP address in the subject name, enter no. When prompted to Display the Certificate Request to terminal, enter yes.

4. Copy the contents of the Certificate Request. Be sure to include:

```
-----BEGIN CERTIFICATE REQUEST-----
```

```
-----END CERTIFICATE REQUEST-----
```

5. Save the contents in a file and securely distribute it to your PKI administrator for signing by the subordinate CA. Once signed, your PKI administrator will need to provide the certificate in PEM format.
6. Import the signed certificate to the subordinate trustpoint

```
SWITCH(config)# crypto pki import <subordinate trustpoint name> certificate
```

7. When prompted enter the base 64 encoded device certificate. End with a blank line or the word "quit" on a line by itself. The Switch should respond with:

```
"% Router Certificate successfully imported"
```

8. Configure the trustpoints to perform revocation checking using CRL

```
SWITCH(config)# crypto pki trustpoint <root trustpoint name>
```

```
SWITCH(ca-trustpoint)# revocation-check CRL
```

```
SWITCH(ca-trustpoint)# crl cache none
```

```
SWITCH(ca-trustpoint)# match key-usage cRLSign
```

```
SWITCH(ca-trustpoint)# exit
```

```
SWITCH(config)# crypto pki trustpoint <subordinate trustpoint name>
```

```
SWITCH(ca-trustpoint)# revocation-check CRL
```

```
SWITCH(ca-trustpoint)# crl cache none
```

```
SWITCH(ca-trustpoint)# match key-usage cRLSign
```

```
SWITCH(ca-trustpoint)# exit
```

### 4.2.19.3. IKEv2

This section discusses IKEv2 which requires configuring an IKEv2 Proposal, Policy, Keyring, and Profile.

1. Configure the IKEv2 Proposal. An IKEv2 proposal is regarded as complete only when it has at least an encryption algorithm, an integrity algorithm, and a Diffie-Hellman (DH) group configured. If no proposal is configured and attached to an IKEv2 policy, then the default proposal is used in the negotiation, and it contains selections that are not valid for the TOE. Thus the following settings must be set in configuring the IPsec with IKEv2 functionality for the TOE:

- a. In privileged EXEC mode, enter configure terminal.

```
SWITCH# configure terminal
```

- b. Specify the IKEv2 proposal. The IKEv2 proposal MUST have a set of an encryption algorithms, a set of integrity or PRF algorithms, and a DH group configured.

```
SWITCH(config)# crypto ikev2 proposal <name>
```

- c. Set the encryption algorithm(s) for the proposal. Choose one of the following:

```
SWITCH(config-ikev2-proposal)# encryption <aes-cbc-128 aes-cbc-256>
```

```
SWITCH(config-ikev2-proposal)# encryption <aes-gcm-128 aes-gcm-256>
```

```
SWITCH(config-ikev2-proposal)# encryption <aes-cbc-256>
```

```
SWITCH(config-ikev2-proposal)# encryption <aes-gcm-256>
```

**Note:** If the IKEv2 proposal is set to aes-cbc-128 or aes-gcm-128, then the IPsec transform set must also be set to esp-aes 128 or esp-gcm 128, respectively. If the IKEv2 proposal is set to aes-cbc-256, then the IPsec transform set can be set to either esp-aes 128 or esp-aes 256. Similarly, if the IKEv2 proposal is set to aes-gcm-256, then the IPsec transform set can be set to either esp-gcm 128 or esp-gcm 256.

IPsec transform sets are configured in the next section.

**Note:** CNSS customers that require conformance to Commercial Solutions for Classified Program (CSfC) program, the encryption algorithm must be either encryption aes-gcm-256 or aes-cbc-256

- d. Set the PRF or integrity algorithm(s) for the proposal. This is dependent on the mode of encryption selected in the step above. If you selected aes-cbc-128 or aes-cbc-256 then you must provide an integrity algorithm:

```
SWITCH(config-ikev2-proposal)# integrity <sha256>
```

If you selected aes-gcm-128 or aes-gcm-256 then you must provide a PRF algorithm

```
SWITCH(config-ikev2-proposal)# prf <sha256>
```

- e. Set the Diffie-Hellman group(s)

```
SWITCH(config-ikev2-proposal)# group 19 20
```

- f. Enter exit to return to the main configuration mode.

```
SWITCH(config-ikev2-proposal)# exit
```

2. Configure the IKEv2 Policy



- a. Define the IKEv2 policy name.  

```
SWITCH(config)# crypto ikev2 policy <Name of IKEv2 policy>
```
- b. Specify the proposal created in the previous section  

```
SWITCH(config-ikev2-policy)# proposal <name>
```
- c. Enter exit to return to the main configuration mode  

```
SWITCH(config-ikev2-policy)# exit
```
3. Configure the IKEv2 Profile. An IKEv2 profile is a repository of nonnegotiable parameters of the IKE SA (such as local/remote identities and authentication methods) and the services available to the authenticated peers that match the profile. An IKEv2 profile must be configured and must be attached to either a crypto map or an IPsec profile on both the IKEv2 initiator and responder.
  - a. Define the IKEv2 Profile.  

```
SWITCH(config)# crypto ikev2 profile <name of IKEv2 profile>
```
  - b. Set the local authentication method.  

```
SWITCH(config-ikev2-profile)# authentication local <rsa-sig>
```
  - c. Set the remote authentication method.  

```
SWITCH(config-ikev2-profile)# authentication remote <rsa-sig>
```
  - d. Specify the local IKE FQDN identity to use.  

```
SWITCH(config-ikev2-profile)# identity local fqdn <fully qualified domain name string>
```
  - e. Set the IKE SA lifetime in seconds.  

```
SWITCH(config-ikev2-profile)# lifetime <120-86400>
```
  - f. Enter exit to return to the main configuration mode  

```
SWITCH(config-ikev2-profile)# exit
```

#### 4.2.19.4. IPsec Transform Sets and SA Lifetimes

The Switch must be configured with the proper transform for IPsec ESP encryption and integrity as well as IPsec lifetimes. During the IPsec SA negotiation, the peers agree to use a particular transform set for protecting a particular data flow.

The Administrator can specify multiple transform sets and then specify one or more of these transform sets in a crypto map entry. The transform set defined in the crypto map entry is used in the IPsec SA negotiation to protect the data flows specified by that crypto map entry's access list.

During IPsec security association negotiations with IKE, peers search for a transform set that is the same at both peers. When such a transform set is found, it is selected and applied to the protected traffic as part of both peers' IPsec SAs. (With manually established SAs, there is no negotiation with the peer, so both sides must specify the same transform set.)

1. Define the allowed transform sets. . The evaluated configuration supports the following:

```
SWITCH(config)# crypto ipsec transform-set <transform set tag> esp-aes 128 esp-sha256-hmac
```

```
SWITCH(config)# crypto ipsec transform-set <transform set tag> esp-gcm 128
```

```
SWITCH(config)# crypto ipsec transform-set <transform set tag> esp-gcm 256
```

**Note:** If the IKEv2 proposal is set to aes-cbc-128 or aes-gcm-128, then the IPsec transform set must also be set to esp-aes 128 or esp-gcm 128, respectively. If the IKEV2 proposal is set to aes-cbc-256, then the IPsec transform set can be set to either esp-aes 128 or esp-aes 256. Similarly, if the IKEV2 proposal is set to aes-gcm-256, then the IPsec transform set can be set to either esp-gcm 128 or esp-gcm 256.

IKEv2 proposals were configured in the preceding section.

2. Define the IPsec mode which is either tunnel mode or transport mode.

```
SWITCH(cfg-crypto-trans)# mode <transport | tunnel>
```

3. Type exit to return to the main configuration mode.

```
SWITCH(cfg-crypto-trans)# exit
```

4. Define the IPsec security association lifetime. The lifetime can be chosen based on time (hours) or can be volume based. A time-based lifetime must be entered in seconds where 1 hour=3600 seconds and 8 hours=28800 seconds.

```
SWITCH(config)# crypto ipsec security-association lifetime <seconds < 120-28800>> | <kilobytes <2560-4294967295>>
```

#### 4.2.19.5. IPsec Crypto Map and Access Control List

The administrator can define the traffic that needs to be protected between two IPsec peers by configuring access lists and applying these access lists to interfaces using crypto map sets. Therefore, traffic may be selected on the basis of the source and destination address, and optionally the Layer 4 protocol and port. (The access lists used for IPsec are only used to determine the traffic that needs to be protected by IPsec, not the traffic that should be blocked or permitted through the interface. Separate access lists define blocking and permitting at the interface).

```
SWITCH(config)# access-list <IP access-list number> permit ip 192.168.3.0 0.0.0.255 10.3.2.0 0.0.0.255
```

For example, if your syslog host is 10.83.84.76 you could define an access list 102 as:

```
SWITCH(config)# access-list 102 permit ip any host 10.83.84.76
```

When a packet matches a permit entry in a particular access list, the method of security in the corresponding crypto map is applied. If the crypto map entry is tagged as ipsec-isakmp, IPsec is triggered. For example:

```
SWITCH(config)# crypto map <crypto map tag> <sequence number> ipsec-isakmp
```

The match address command specifies to use access list number order to determine which traffic is relevant.

```
SWITCH(config-crypto-map)# match address <IP access-list number>
```

Crypto map entries also include transform sets. A transform set is an acceptable combination of security protocols, algorithms, and other settings that can be applied to IPsec-protected traffic. During the IPsec SA negotiation, the peers agree to use a particular transform set when protecting a particular data flow. Use the set transform-set command specifies the transform set tag.

```
SWITCH(config-crypto-map)# set transform-set <proposal tag>
```

The set peer command specifies the ip address of the peer

```
SWITCH(config-crypto-map)# set peer <IP address of peer>
```

If using IKEv2 the set ikev2-profile command specifies the profile to use

```
SWITCH(config-crypto-map)# set ikev2-profile <name of the ikev2 profile>
```

You will need to apply the crypto map to an interface. The GigabitEthernet1 interface configured earlier may be used.

```
SWITCH(config)# int GigabitEthernet1
```

```
SWITCH(config-if)# crypto map <crypto map tag>
```

```
SWITCH(config-if)# end
```

A crypto map set can contain multiple entries, each with a different access list. The crypto map entries are searched in a sequence-- the router attempts to match the packet to the access list specified in that entry.

When a packet matches a permit entry in a particular access list, and the corresponding crypto map entry is tagged connections are established, if necessary. If the crypto map entry is tagged as ipsec-isakmp, IPsec is triggered.

If there is no SA that the IPsec can use to protect this traffic to the peer, IPsec uses IKE to negotiate with the remote peer to set up the necessary IPsec SAs on behalf of the data flow. The negotiation uses information specified in the crypto map entry as well as the data flow information from the specific access list entry.

Once established, the set of SAs (outbound to the peer) is then applied to the triggering packet and to subsequent applicable packets as those packets exit the Switch. "Applicable" packets are packets that match the same access list criteria that the original packet matched. For example, all applicable packets could be encrypted before being forwarded to the remote peer. The corresponding inbound SAs are used when processing the incoming traffic from that peer.

Access lists associated with IPsec crypto map entries also represent the traffic that the Switch needs protected by IPsec. Inbound traffic is processed against crypto map entries. If an unprotected packet matches a permit entry in a particular access list associated with an IPsec crypto map entry, that packet is dropped because it was not sent as an IPsec-protected packet.

Traffic that does not match a permit crypto map ACL and does not match a non-crypto permit ACL on the interface would be DISCARDED. For example:

```
SWITCH(config)# access-list 102 permit ip 192.168.3.0 0.0.0.255
```

```
SWITCH(config)# access-list 103 permit ip 192.168.4.0 0.0.0.255
```

In the example above host 10.83.84.76 does not match either access-list.

Traffic that does not match a permit ACL in the crypto map, but does match a non-crypto permit ACL would be allowed to BYPASS the tunnel. For example, a non-crypto permit ACL for ICMP would allow ping traffic to flow unencrypted if a permit crypto map was not configured that matches the ping traffic. For example:

```
SWITCH(config)# access-list 102 permit ip 192.168.3.0 0.0.0.255
```

```
SWITCH(config)# access-list 103 permit ip any host 10.83.84.76
```

In the example above host 10.83.84.76 matches access-list 103 and will bypass the tunnel.

For additional information on Access Control Lists and how rule processing impacts the processing of an IP packet refer to the "ACLs" Chapter of [4]. If you downloaded the entire contents of [4] in PDF format the "ACLs" is in Chapter 19 for IPv4 and 20 for IPv6.

#### 4.2.19.6. Security Policy Database (SPD)

RFC 4301 calls for an IPsec implementation to protect IP traffic through the use of a Security Policy Database (SPD). The SPD is used to define how IP packets are to be handled: PROTECT the packet (e.g., encrypt the packet), BYPASS the IPsec services (e.g., no encryption), or DISCARD the packet (e.g., drop the packet).

The traffic matching permit ACL would then flow through the IPsec tunnel and be classified as “PROTECTED”.

Traffic that does not match a permit crypto map ACL and does not match a non-crypto permit ACL on the interface would be DISCARDED.

Traffic that does not match a permit ACL in the crypto map, but does match a non-crypto permit ACL would be allowed to BYPASS the tunnel. For example, a non-crypto permit ACL for ICMP would allow ping traffic to flow unencrypted if a permit crypto map was not configured that matches the ping traffic.

### 4.2.19.7. Configure Reference Identifier

If you are using X.509 certificates for IKE peer authentication this section describes configuration of the peer reference identifier through use of a certificate map. Certificate maps provide the ability for a certificate to be matched with a given set of criteria. You can specify which fields within a certificate should be checked and which values those fields may or may not have. There are six logical tests for comparing the field with the value: equal, not equal, contains, does not contain, less than, and greater than or equal. The subordinate trustpoint can bind themselves to certificate maps, and the Switch will determine if they are valid during IKE authentication.

1. Start certificate-map mode

```
SWITCH(config)# crypto pki certificate map <attribute map tag> | <sequence-number>
```

2. Specify one or more certificate fields together with their matching criteria and the value to match. In the evaluated configuration, the field name must specify the SAN (alt-subject-name) field of the peer’s certificate. Match criteria should be “eq” for equal.

For example:

```
SWITCH(ca-certificate-map)# alt-subject-name eq <FQDN of Peer SAN field>
```

```
SWITCH(ca-certificate-map)# alt-subject-name eq < IP Address of Peer in SAN field>
```

3. Type exit to return to the main configuration mode.

```
SWITCH(ca-certificate-map)# exit
```

4. Associate the certificate map to the IPsec trustpoint created in section 4.2.19.2

```
SWITCH(config)# crypto pki trustpoint < subordinate trustpoint name>
```

```
SWITCH(ca-trustpoint)# match certificate <attribute map tag>
```

### 4.2.19.8. IKEv2 Fragmentation

Enable support for both the Cisco proprietary IKEv2 fragmentation methodology and the IETF fragmentation methodology specified in RFC 7383.

```
SWITCH#(config)# crypto ikev2 fragmentation
```

The IETF method encrypts packets after fragmentation whereas the Cisco proprietary method performs fragmentation on the encrypted packet. This command expands interoperability between a Cisco device and a non-Cisco host.

### 4.2.19.9. Enable Remote Syslog Server

Once IPsec has been setup and configured to protect the transmission of audit events to the remote syslog server, use the logging host command below to enable the TOE to transmit audit data. When an audit event is generated, is it simultaneously sent to the external server and the local store.

To configure a remote syslog server enter the following command:

```
SWITCH(config)# logging host <ip address>
```

## 4.2.20. MACSEC and MKA Configuration

The TOE authenticates and encrypts packets between itself and a MACsec peer. The MACsec Key Agreement (MKA) Protocol provides the required session keys and manages the required encryption keys to protect data exchanged by the peers. By default, MACsec is disabled and there are no MKA policies configured on the TOE.

The following is an example of an MKA policy:

```
SWITCH(config)# mka policy <policy-name>
SWITCH(config-mka-policy)# key-server priority 200
SWITCH(config-mka-policy)# macsec-cipher-suite gcm-aes-128
SWITCH(config-mka-policy)# confidentiality-offset 30
SWITCH(config-mka-policy)# end
```

The following is an example of configuring MACsec PSK

```
SWITCH(config)# key chain keychain1 macsec
SWITCH(config-key-chain)# key 1000
SWITCH(config-key-chain)# cryptographic-algorithm aes-128-cmac
SWITCH(config-key-chain)# key-string 12345678901234567890123456789012
SWITCH(config-key-chain)# lifetime local 12:12:00 October 2 2022 12:19:00 October 2
203
SWITCH(config-mka-policy)# end
```

**Note:** When specifying the value of the key identifier, the Administrator must ensure the length does not exceed 64 hex digits (32 bytes). An example of the maximum length would be:

```
key abcdef0123456789abcdef0123456789abcdef0123456789abcdef0123456789
```

The following is an example of configuring MACsec MKA on an Interface using PSK

```
SWITCH(config) interface GigabitEthernet1
SWITCH(config-if)# macsec network-link
SWITCH(config-if)# mka policy my_policy
SWITCH(config-if)# mka pre-shared-key key-chain mykeychain1
SWITCH(config-if)# macsec replay-protection window-size 10
SWITCH(config-if)# end
```

Detailed steps to configure MACsec and an MKA policy on the TOE can be found in the “Configuring MACsec Encryption” Chapter of [4]. If you downloaded the entire contents of [4] in PDF format the “Configuring MACsec Encryption” is in Chapter 12.

Configuration Examples for MACsec Encryption can be found in the "Configuration Examples for MACsec Encryption" section of the "Configuring MACsec Encryption" Chapter of [4]. If you downloaded the entire contents of [4] in PDF format the “Configuring MACsec Encryption” is in Chapter 12.

To verify MACsec is enabled, refer to the "show" commands listed under **Step 2** of [Scenario 2](#) in [8].

### 4.2.21. Protect CAK Data

To ensure MACsec CAK Data is protected from unauthorized disclosure perform the following steps:

1. In privilege EXEC mode, enter configure terminal

```
SWITCH# config terminal
```

2. Create the following Embedded Event Manager applet for the running-configuration:

```
SWITCH(config)#event manager applet SHOW_RUN_NO_KEY_STRING
SWITCH(config-applet)# event cli pattern "show run" sync yes
SWITCH(config-applet)# action 1.0 cli command "enable"
SWITCH(config-applet)# action 2.0 cli command "show run | exclude key-string"
SWITCH(config-applet)# action 3.0 puts "$_cli_result"
SWITCH(config-applet)# action 4.0 set $_exit_status "0"
SWITCH(config-applet)# exit
```

3. Create the following Embedded Event Manager applet for the startup-configuration:

```
SWITCH(config)#event manager applet SHOW_STARTUP_NO_KEY_STRING
SWITCH(config-applet)# event cli pattern "show start" sync yes
SWITCH(config-applet)# action 1.0 cli command "enable"
SWITCH(config-applet)# action 2.0 cli command "show start | exclude key-string"
SWITCH(config-applet)# action 3.0 puts "$_cli_result"
SWITCH(config-applet)# action 4.0 set $_exit_status "0"
SWITCH(config-applet)# end
```

### 4.2.22. FIPS Mode

The administrator needs to configure the Switch for FIPS mode of operation.

4. In privilege EXEC mode, enter configure terminal

```
SWITCH# config terminal
```

5. Enter a FIPS authorization key. **Note:** The key length should be 32 characters. **Note:** If you have High Availability enabled ensure both active and standby Switches have the same FIPS authorization key.

```
SWITCH(config)# fips authorization-key 12345678901234567890123456789012
```

6. Exit configuration mode and return to privileged EXEC mode

```
SWITCH(config)# end
```

7. You must now reboot the switch to enable FIPS mode.

### 4.2.23. Verify FIPS Mode

To verify FIPS mode enter the following

```
SWITCH# show fips status
```

The status of FIPS mode on the device will be displayed

For additional information, refer to the “Secure Operation in FIPS Mode” Chapter of [4]. If you downloaded the entire contents of [4] in PDF format the “Secure Operation in FIPS Mode” is in Chapter 34.

## 5. Operational Guidance for the TOE

### 5.1. Access CLI Over SSH

From your remote management workstation, initiate a connect using SSH and supply either your public key or password credentials. Upon successful login you will be presented with privilege administrator access denoted by the ‘hashtag’ symbol:

```
SWITCH#
```

### 5.2. View Audit Events

Audit events may be viewed at the CLI by entering:

```
SWITCH# show logging
```

### 5.3. Unblock Locked-Out Account

To unblock an account that has been prevented from logging in due to successive login failures enter the following:

```
SWITCH# clear aaa local user blocked username <username>
```

### 5.4. Cryptographic Self-Tests

The TOE runs a suite of self-tests during initial start-up to verify correct operation of cryptographic modules. If any component reports failure for the POST, the system crashes and appropriate information is displayed on the local console. All ports are blocked from moving to forwarding state during the POST. If all components of all modules pass the POST, the system is placed in FIPS PASS state and ports are allowed to forward data traffic. If any of the tests fail, a message is displayed to the local console and the TOE component will automatically reboot. If the Administrator observes a cryptographic self-test failure, they must contact Cisco Technical Support. Refer to the Contact Cisco section of this document.

If the Administrator needs to execute cryptographic self-tests for the Switch after the image is loaded enter the following command:

```
SWITCH# test crypto self-test
```

### 5.5. Zeroize Private Key

Should the Administrator need to zeroize a private key generated as instructed in the SSH sections of this document and stored in NVRAM, the following command may be used in configuration mode:

```
SWITCH(config)# crypto key zeroize rsa <key pair label>
```

The keys are zeroized immediately after use.

Other keys stored in SDRAM are zeroized when no longer in use, zeroized with a new value of the key, or zeroized on power-cycle.

## 5.6. MACsec Session Interruption and Recovery

If a MACsec session with a peer is unexpectedly interrupted, the connection will be broken and the Administrator will find a connection time out error message in the audit log. The administrator can use the show command below to confirm the connection is broken:

```
SWITCH# show mka statistics
```

```
SWITCH# show mka sessions
```

```
SWITCH# show mka statistics
```

When a connection is broken no administrative interaction is required. The MACsec session will be reestablished once the peer is back online.

## 5.7. IPsec Session Interruption and Recovery

If an IPsec session with a peer is unexpectedly interrupted, the connection will be broken and the Administrator will find a connection time out error message in the audit log. The administrator can use the show command below to confirm the connection is broken:

```
SWITCH# show crypto ipsec sa
```

When a connection is broken no administrative interaction is required. The IPsec session will be reestablished (a new SA set up) once the peer is back online.

## 5.8. Update TOE Software

Using the CLI, the Administrator may install new image files in one stage (all at once) or may choose to perform a multi-stage upgrade.

### 5.8.1. One-Shot Upgrade

1. Follow the steps below to update the TOE Software in one stage (all at once) using the CLI.
  - a. You will need to obtain an updated 17.12 software image. Navigate to Cisco Software Central at [https://software.cisco.com/software/cswws/platform/home?locale=en\\_US#](https://software.cisco.com/software/cswws/platform/home?locale=en_US#). Use your Cisco Care Online (CCO) or SMART account and download the image for your Switch platform.
  - b. Place the image on a TFTP, FTP, or SFTP server that is reachable by the SWITCH.
  - c. To query the currently active software version at the SWITCH console enter:  

```
SWITCH# show version
```
  - d. At the SWITCH console enter: 

```
install add file [tftp | ftp | sftp://<IP Address of TFTP/FTP/SFTP server>] <image name.bin> activate commit
```

The image installation process will begin.
  - e. Respond “y” to the prompt. The SWITCH will commit the new image, save the configuration, and reload.  
**Note:** Since the update process involves rebooting before an upgrade can be completed, the TOE will cease to pass traffic during the update.  
**Note:** If you respond with a ‘n’ the SWITCH software will not be upgraded.
2. The TOE will automatically verify the integrity of the stored image when loaded for execution.



The SWITCH uses a Cisco public key to validate the digital signature to obtain an embedded SHA512 hash that was generated prior to the image being distributed from Cisco. The SWITCH then computes its own hash of the image using the same SHA512 algorithm. The SWITCH verifies the computed hash against the embedded hash. If they match the image is authenticated and has not been modified or tampered. If they do not match the image will not boot or execute.

After boot, the authorized administrator can also manually verify the digital signature by executing on the SWITCH:

```
verify bootflash:<image or package name>
```

## 5.8.2. Multi-Stage Upgrade

1. Follow the steps below to update the TOE Software in separate stages:
  - a. You will need to obtain an updated 17.12 software image. Navigate to Cisco Software Central at [https://software.cisco.com/software/cswws/ws/platform/home?locale=en\\_US#](https://software.cisco.com/software/cswws/ws/platform/home?locale=en_US#). Use your Cisco Care Online (CCO) or SMART account and download the image for your Switch platform.
  - b. Place the image on a TFTP, FTP, or SFTP server that is reachable by the SWITCH.
  - c. To query the currently active software version at the SWITCH console enter:
 

```
SWITCH# show version
```
  - d. At the SWITCH console enter: `SWITCH# copy tftp bootflash:`

The SWITCH will prompt for address or name of remote host. Enter the IP address of your TFTP Sever. Once the image has successfully downloaded, the Predownload Status will change to “Complete”

The SWITCH will prompt for Source filename. Enter the name of the bin image file.

The SWITCH will begin loading the image via TFTP to bootflash:
  - e. At the SWITCH console enter: `install add file bootflash: cat9k_lite_iosxe.17.12.03.SPA.bin`

The SWITCH will begin installing the image file. It should respond that the image was successfully added and will display the version.
  - f. At the SWITCH console enter: `install activate`

The SWITCH should respond with “System configuration has been modified”

Press Yes(y) to save the configuration and proceed.
  - g. The SWITCH console will respond with “This operation may require a reload of the system. Do you want to proceed? [y/n]”
  - h. Respond with a ‘y’ to the prompt. The SWITCH will begin activating the image package and should respond with a list of the packages that it activated. The SWITCH console will then respond with a message stating the Activate stage finished and that it will now reload.
 

**Note:** Since the update process involves rebooting before an upgrade can be completed, the TOE will cease to pass traffic during the update

**Note:** If you respond with a ‘n’ the SWITCH software will not be upgraded.
  - i. After the SWITCH has reloaded, access the CLI console and enter the following to commit the image:
 

```
SWITCH# install commit
```

The SWITCH should respond that it successful committed the package.

- The administrator can verify the image is installed and activated on the SWITCH by entering:

```
SWITCH# show install summary
```

The image Filename/Version should say "C" for activated and committed.

**Note:** At installation, the SWITCH extracts sub-packages from the image file that was installed (.bin) and the SWITCH boots using a package provisioning file, packages.conf. This provisioning file manages the bootup of each individual sub-package.

If desired, the authorized administrator can manually verify the digital signature on each individual sub-package by executing verify bootflash:<package name> on the SWITCH.

For example on the 9200CX:

```
SWITCH# verify bootflash:cat9k_lite-rpboot.17.12.03.SPA.pkg
```

```
SWITCH# verify bootflash:cat9k_lite-rbase.17.12.03.SPA.pkg
```

For example on the 9300X/9300LM/9500X:

```
SWITCH# verify bootflash:cat9k-rpboot.17.12.03.SPA.pkg
```

```
SWITCH# verify bootflash:cat9k-rbase.17.12.03.SPA.pkg
```

The TOE will automatically verify the integrity of the stored image when loaded for execution.

The TOE uses a Cisco public key to validate the digital signature to obtain an embedded SHA512 hash that was generated prior to the image being distributed from Cisco. The TOE then computes its own hash of the image using the same SHA512 algorithm and verifies the computed hash against the embedded hash. If they match the image is authenticated and has not been modified or tampered. If they do not match the image will not boot or execute.

After boot, the authorized administrator can also manually verify the digital signature by executing on the TOE:

```
verify bootflash:<image or package name>
```

## 6. Auditing

Auditing allows Security Administrators to discover intentional and unintentional issues with the TOE's configuration and/or operation. Auditing of administrative activities provides information that may be used to hasten corrective action should the system be configured incorrectly. Security audit data can also provide an indication of failure of critical portions of the TOE (e.g. a communication channel failure or anomalous activity (e.g. establishment of an administrative session at a suspicious time, repeated failures to establish sessions or authenticate to the TOE) of a suspicious nature.

The TOE generates an audit record whenever an audited event occurs. The types of events that cause audit records to be generated include, cryptography related events, identification and authentication related events, and administrative events (the specific events and the contents of each audit record are listed in the table below). Each of the events is specified in enough detail to identify the user for which the event is associated, when the event occurred, where the event occurred, the outcome of the event, and the type of event that occurred.

The Switch, which is the component that stores audit data locally, will also transmit all audit messages in real-time to a specified external syslog server.

**Table 5. Sample Audit Events**

SFR	Auditable Event and Additional Audit Record Content	Sample Audit Event Data

FAU_GEN.1.1 FAU_GEN.1.1/MACSEC	Startup and Shutdown of Audit Function	<pre>&lt;189&gt;261: C9200-24T: Nov  9 2022 14:34:14: %SYS-5-RESTART: System restarted -- &lt;190&gt;268: C9200-24T: Nov  9 2022 14:34:14: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 172.16.16.239 port 514 started - CLI initiated &lt;190&gt;12092: C9200-24T: Apr 11 2023 07:46:08: %HA_EM-6-LOG: cli_log: User:admin via Port:0 Executed[reload ]</pre>
FCS_IPSEC_EXT.1	Failure to establish an IPsec SA with reason for failure.	<pre><b><u>Failed to find matching policy (General)</u></b> &lt;191&gt;14204: C9200-24T: Nov  9 2022 04:37:26: IKEv2:(SESSION ID = 72,SA ID = 1):Received Packet [From 192.168.144.254:4500/To 192.168.144.10:4500/VRF i0:f0] &lt;187&gt;14266: C9200-24T: Nov  9 2022 04:38:24: %IKEV2-3-NEG_ABORT: Negotiation aborted due to ERROR: Failed to find a matching policy  <b><u>Invalid transform proposal received (bad ESP cipher)</u></b> &lt;191&gt;15522: C9200-24T: Nov  9 2022 07:45:51: IKEv2:(SESSION ID = 85,SA ID = 1):Received Packet [From 192.168.144.254:4500/To 192.168.144.10:4500/VRF i0:f0] &lt;191&gt;15563: C9200-24T: Nov  9 2022 07:45:51: IPSEC(ipsec_process_proposal): invalid transform proposal received: &lt;191&gt;15564: C9200-24T:      {esp-aes 256 esp-sha-hmac } &lt;191&gt;15566: C9200-24T: Nov  9 2022 07:45:51: IKEv2-ERROR:(SESSION ID = 85,SA ID = 1):Received Policies: : Failed to find a matching policy  <b><u>Failed to find matching proposal (bad IKE cipher)</u></b> &lt;191&gt;5794: C9200-24T: Apr 19 2023 09:43:04: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;191&gt;5804: C9200-24T: Apr 19 2023 09:43:04: IKEv2-ERROR:(SESSION ID = 8,SA ID = 1):Received Policies: : Failed to find a matching policyProposal 1: AES-CBC-192 SHA256 SHA256 DH_GROUP_2048_MODP/Group 14 &lt;191&gt;5805: C9200-24T: Apr 19 2023 09:43:04: IKEv2-ERROR:(SESSION ID = 8,SA ID = 1):Expected Policies: : Failed to find a matching policyProposal 1: AES-CBC-128 AES-CBC-256 SHA256 SHA96 SHA256 SHA512 DH_GROUP_2048_MODP/Group 14 &lt;191&gt;5807: C9200-24T: Apr 19 2023 09:43:04: IKEv2:(SESSION ID = 8,SA ID = 1):Sending no proposal chosen notify  <b><u>Failed to validate certificate (Bad Reference Identifier)</u></b> &lt;191&gt;6044: C9200-24T: Feb 23 2023 18:30:45: IKEv2:(SESSION ID = 17,SA ID = 1):Received Packet [From 192.168.144.254:4500/To 192.168.144.10:4500/VRF i0:f0] &lt;191&gt;6182: C9200-24T: Feb 23 2023 18:30:45: CRYPTO_PKI: Checking cert map authorization &lt;187&gt;6185: C9200-24T: Feb 23 2023 18:30:45: %PKI-3-CERTIFICATE_INVALID_UNAUTHORIZED: Certificate chain validation has failed. Unauthorized</pre>

FCS_SSHS_EXT.1	Failure to establish an SSH session; Reason for failure	<p><b><u>No matching cipher</u></b></p> <pre>&lt;187&gt;1137: C9200-24T: Apr 13 2023 03:29:49: %SSH-3-NO_MATCH: No matching cipher found: client aes128-ctr server aes256-cbc,aes128-cbc &lt;189&gt;1138: C9200-24T: Apr 13 2023 03:29:49: %SSH-5-SSH2_SESSION: SSH2 Session request from 172.16.16.254 (tty = 0) using crypto cipher '', hmac '' Failed &lt;189&gt;1139: C9200-24T: Apr 13 2023 03:29:49: %SSH-5-SSH2_CLOSE: SSH2 Session from 172.16.16.254 (tty = 0) for user '' using crypto cipher '', hmac '' closed</pre> <p><b><u>No matching host key type</u></b></p> <pre>&lt;187&gt;1140: C9200-24T: Apr 13 2023 03:43:15: %SSH-3-NO_MATCH: No matching hostkey algorithm found: client ssh-rsa server rsa-sha2-256,rsa-sha2-512 &lt;189&gt;1141: C9200-24T: Apr 13 2023 03:43:15: %SSH-5-SSH2_SESSION: SSH2 Session request from 172.16.16.254 (tty = 0) using crypto cipher '', hmac '' Failed &lt;189&gt;1142: C9200-24T: Apr 13 2023 03:43:15: %SSH-5-SSH2_CLOSE: SSH2 Session from 172.16.16.254 (tty = 0) for user '' using crypto cipher '', hmac '' closed</pre> <p><b><u>No matching MAC</u></b></p> <pre>&lt;187&gt;1143: C9200-24T: Apr 13 2023 04:04:18: %SSH-3-NO_MATCH: No matching mac found: client hmac-sha1 server hmac-sha2-512,hmac-sha2-256 &lt;189&gt;1144: C9200-24T: Apr 13 2023 04:04:18: %SSH-5-SSH2_SESSION: SSH2 Session request from 172.16.16.254 (tty = 0) using crypto cipher '', hmac '' Failed &lt;189&gt;1145: C9200-24T: Apr 13 2023 04:04:18: %SSH-5-SSH2_CLOSE: SSH2 Session from 172.16.16.254 (tty = 0) for user '' using crypto cipher '', hmac '' closed</pre> <p><b><u>No matching key exchange method</u></b></p> <pre>&lt;187&gt;1146: C9200-24T: Apr 13 2023 04:15:20: %SSH-3-NO_MATCH: No matching kex algorithm found: client ecdh-sha2-nistp256,ext-info-c server diffie-hellman-group14-sha1 &lt;189&gt;1147: C9200-24T: Apr 13 2023 04:15:20: %SSH-5-SSH2_SESSION: SSH2 Session request from 172.16.16.254 (tty = 0) using crypto cipher '', hmac '' Failed &lt;189&gt;1148: C9200-24T: Apr 13 2023 04:15:20: %SSH-5-SSH2_CLOSE: SSH2 Session from 172.16.16.254 (tty = 0) for user '' using crypto cipher '', hmac '' closed</pre> <p><b><u>Oversized Packet</u></b></p> <pre>&lt;187&gt;1120: C9200-24T: Apr 13 2023 03:00:02: %SSH-3-BAD_PACKET_LEN: Bad packet length 33068 &lt;190&gt;1121: C9200-24T: Apr 13 2023 03:00:02: %SYS-6-LOGOUT: User admin has exited tty session 2(172.16.16.254)</pre>
----------------	---	--

FIA_AFL.1	Failed Login due to Exceeding limit	<pre>&lt;189&gt;676: C9200-24T: Mar 28 2023 05:36:21: %AAA-5- LOCAL_USER_BLOCKED: User TestUser17482 blocked for login till 00:37:21 EST Mar 28 2023 &lt;188&gt;677: C9200-24T: Mar 28 2023 05:36:23: %SEC_LOGIN- 4-LOGIN_FAILED: Login failed [user: TestUser17482] [Source: 172.16.16.254] [localport: 22] [Reason: Login Authentication Failed] at 00:36:23 EST Tue Mar 28 2023</pre>
FIA_UIA_EXT.1 FIA_UAU_EXT.2	All use of the authentication mechanism.	<pre><b><u>SSH Authentication Success - Password</u></b> &lt;189&gt;11203: C9200-24T: Apr 6 2023 04:25:53: %SEC_LOGIN- 5-LOGIN_SUCCESS: Login Success [user: admin] [Source: 172.16.16.254] [localport: 22] at 23:25:53 EST Wed Apr 5 2023 &lt;189&gt;11204: C9200-24T: Apr 6 2023 04:25:53: %SSH-5- SSH2_USERAUTH: User 'admin' authentication for SSH2 Session from 172.16.16.254 (tty = 0) using crypto cipher 'aes256-cbc', hmac 'hmac-sha2-256' Succeeded SSH Authentication Failure - Password &lt;188&gt;1179: C9200-24T: Apr 13 2023 05:08:12: %SEC_LOGIN- 4-LOGIN_FAILED: Login failed [user: admin] [Source: 172.16.16.254] [localport: 22] [Reason: Login Authentication Failed] at 00:08:12 EST Thu Apr 13 2023 &lt;189&gt;1180: C9200-24T: Apr 13 2023 05:08:12: %SSH-5- SSH2_USERAUTH: User '' authentication for SSH2 Session from 172.16.16.254 (tty = 0) using crypto cipher 'aes256-cbc', hmac 'hmac-sha2-256' Failed  <b><u>SSH Authentication Success - Public Key</u></b> &lt;189&gt;12011: C9200-24T: Apr 11 2023 02:32:53: %SEC_LOGIN- 5-LOGIN_SUCCESS: Login Success [user: testadmin] [Source: 172.16.16.254] [localport: 22] at 21:32:53 EST Mon Apr 10 2023 &lt;189&gt;12012: C9200-24T: Apr 11 2023 02:32:53: %SSH-5- SSH2_USERAUTH: User 'testadmin' authentication for SSH2 Session from 172.16.16.254 (tty = 0) using crypto cipher 'aes256-cbc', hmac 'hmac-sha2-256' Succeeded  <b><u>SSH Authentication Failure - Public Key</u></b> &lt;188&gt;12044: C9200-24T: Apr 11 2023 02:35:27: %SEC_LOGIN- 4-LOGIN_FAILED: Login failed [user: testadmin] [Source: 172.16.16.254] [localport: 22] [Reason: Login Authentication Failed] at 21:35:27 EST Mon Apr 10 2023 &lt;189&gt;12045: C9200-24T: Apr 11 2023 02:36:23: %SSH-5- SSH2_USERAUTH: User '' authentication for SSH2 Session from 172.16.16.254 (tty = 0) using crypto cipher 'aes256-cbc', hmac 'hmac-sha2-256' Failed  <b><u>Console Authentication Success</u></b> &lt;189&gt;2142: C9200-24T: Mar 17 2023 21:39:45: %SEC_LOGIN- 5-LOGIN_SUCCESS: Login Success [user: admin] [Source: LOCAL] [localport: 0] at 16:39:45 EST Fri Mar 17 2023  <b><u>Console Authentication Failure</u></b> &lt;188&gt;2134: C9200-24T: Mar 17 2023 21:34:35: %SEC_LOGIN- 4-LOGIN_FAILED: Login failed [user: admin] [Source: LOCAL] [localport: 0] [Reason: Login Authentication Failed] at 16:34:35 EST Fri Mar 17 2023</pre>

FIA_X509_EXT.1/Rev	Unsuccessful attempt to validate a certificate	<p><b><u>Expired Server Cert</u></b></p> <pre>&lt;191&gt;3207: C9200-24T: Feb  2 2023 03:35:23: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;191&gt;3273: C9200-24T: Feb  2 2023 03:35:23: IKEv2- ERROR:Current time is more than cert validity time Expired SubCA Cert &lt;191&gt;3370: C9200-24T: Feb  2 2023 03:36:17: IKEv2:(SESSION ID = 10,SA ID = 1):Received Packet [From 192.168.144.254:4500/To 192.168.144.10:4500/VRF i0:f0] &lt;187&gt;3478: C9200-24T: Feb  2 2023 03:36:17: %PKI-3- CERTIFICATE_INVALID_EXPIRED: Certificate chain validation has failed. The certificate (SN: 13) has expired. Validity period ended on 2022-11- 29T00:45:00Z</pre> <p><b><u>Absent or invalid basicConstraint flag</u></b></p> <pre>&lt;191&gt;20984: C9200-24T: Apr 20 2023 03:23:13: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;191&gt;21149: C9200-24T: Apr 20 2023 03:23:13: IKEv2:(SESSION ID = 34,SA ID = 1):Verify cert failed &lt;191&gt;21147: C9200-24T: Apr 20 2023 03:23:13: IKEv2:(SA ID = 1):[PKI -&gt; IKEv2] Validation of certificate chain FAILED</pre> <p><b><u>Revoked Certificate</u></b></p> <pre>&lt;47&gt;21682: C9200-24T: Apr 20 2023 03:59:56: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;43&gt;22116: C9200-24T: Apr 20 2023 03:59:56: %PKI-3- CERTIFICATE_REVOKED: Certificate chain validation has failed. The certificate (SN: 00D1) is revoked</pre> <p><b><u>Corrupt Cert ASN1</u></b></p> <pre>&lt;191&gt;10926: C9200-24T: Apr 19 2023 10:18:13: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;191&gt;10988: C9200-24T: Apr 19 2023 10:18:13: CRYPTO_PKI: status = 0x705(E_INPUT_DATA : invalid encoding format for input data): BER/DER decoding of certificate has failed</pre> <p><b><u>Corrupt Cert Signature</u></b></p> <pre>A&lt;47&gt;23331: C9200-24T: Apr 20 2023 05:01:12: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;47&gt;23681: C9200-24T: Apr 20 2023 05:01:13: ../cert- c/source/vericert.c(145) : E_INVALID_SIGNATURE : error verifying digital signature</pre> <p><b><u>Corrupt Public Key</u></b></p> <pre>&lt;47&gt;23744: C9200-24T: Apr 20 2023 05:02:08: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0]</pre>
--------------------	--	---

		<pre>&lt;47&gt;24093: C9200-24T: Apr 20 2023 05:02:09: ../cert- c/source/vericert.c(145) : E_INVALID_SIGNATURE : error verifying digital signature  <b><u>CRL Incorrectly Signed</u></b> &lt;47&gt;22841: C9200-24T: Apr 20 2023 05:00:06: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;47&gt;23249: C9200-24T: Apr 20 2023 05:00:06: Key-usage mismatch. Cert does not have cRLSign bit set. &lt;47&gt;23250: C9200-24T: Apr 20 2023 05:00:06: CRYPTO_PKI: CRL verify has failed  <b><u>Invalid Certificate Chain</u></b> &lt;47&gt;23744: C9200-24T: Apr 20 2023 05:02:08: IKEv2:Received Packet [From 192.168.144.254:500/To 192.168.144.10:500/VRF i0:f0] &lt;47&gt;23909: C9200-24T: Apr 20 2023 05:02:08: IKEv2:(SA ID = 1):[PKI -&gt; IKEv2] Validation of certificate chain FAILED  <b><u>Unreachable Revocation Server</u></b> &lt;191&gt;3149: C9200-24T: Apr 19 2023 09:36:07: IKEv2:(SESSION ID = 4,SA ID = 1):Received Packet [From 192.168.144.254:4500/To 192.168.144.10:4500/VRF i0:f0] &lt;187&gt;3378: C9200-24T: Apr 19 2023 09:36:08: %PKI-3- CRL_FETCH_FAIL: CRL fetch for trustpoint rootca-rsa failed  Add Trust Anchor See FMT_SMF.1  Remove Trust Anchor See FMT_SMF.1</pre>
FMT_MOF.1/ ManualUpdate	Any attempt to initiate a manual update	See FPT_TUD_EXT.1

FMT_SMF.1	All management activities of TSF data.	<p>Ability to administer the TOE locally and remotely See FIA_UIA_EXT.1</p> <p><b><u>Ability to configure the access banner</u></b> &lt;45&gt;179: C9200-24T: Oct 13 2022 17:29:28: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:banner login z This is the CC Login Banner z &lt;45&gt;180: C9200-24T: Oct 13 2022 17:29:33: %SYS-5-CONFIG_I: Configured from console by admin on console</p> <p><b><u>Ability to configure the session inactivity time before session termination or locking</u></b> <b>Console:</b> &lt;189&gt;909: C9200-24T: Mar 28 2023 19:16:15: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:line con 0 &lt;189&gt;910: C9200-24T: Mar 28 2023 19:16:15: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:exec-timeout 1</p> <p><b>SSH:</b> &lt;189&gt;493: C9200-24T: Mar 28 2023 02:01:34: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:line vty 0 15 &lt;189&gt;494: C9200-24T: Mar 28 2023 02:01:34: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:exec-timeout 1</p> <p>Ability to update the TOE, and to verify the updates using [digital signature] capability prior to installing those updates See FPT_TUD_EXT.1</p> <p><b><u>Ability to configure the authentication failure parameters for FIA AFL.1</u></b> &lt;189&gt;624: C9200-24T: Mar 28 2023 05:35:50: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:aaa authentication rejected 3 in 3600 ban 60</p> <p><b><u>Ability to modify the behavior of the transmission of audit data to an external IT entity</u></b> &lt;45&gt;156: C9200-24T: Oct 13 2022 18:26:19: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:logging host 172.16.16.239 vrf Mgmt-vrf transport udp port 514</p> <p><b><u>Ability to manage the cryptographic keys</u></b> <b><u>Generate Crypto Key for SSH:</u></b> &lt;45&gt;342: C9200-24T: Oct 18 2022 20:36:21: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:crypto key generate rsa label * modulus 2048 &lt;45&gt;347: C9200-24T: Oct 18 2022 20:36:57: %CRYPTO_ENGINE-5-KEY_ADDITION: A key named SSH-KEY.server has been generated or imported by crypto-engine</p> <p><b><u>Generate Crypto Key for IPsec:</u></b></p>
-----------	--	--



		<pre> &lt;189&gt;691928: C9200-24T: Oct 25 2022 21:17:25: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:crypto key generate rsa general-keys modulus 2048 label * &lt;189&gt;691926: C9200-24T: Oct 25 2022 21:17:25: %CRYPTO_ENGINE-5-KEY_ADDITION: A key named IPSEC-KEY has been generated or imported by crypto-engine  <b>Delete Crypto Key:</b> &lt;46&gt;24369: C9200-24T: Apr 21 2023 01:45:48: %HA_EM-6- LOG: cli_log: User:admin via Port:0 Executed[crypto key zeroize rsa *] &lt;45&gt;24376: C9200-24T: Apr 21 2023 01:45:50: %CRYPTO_ENGINE-5-KEY_DELETED: A key named SSH-KEY has been removed from key storage  <b>See also audits below for ability to manage the TOE's trust store and the trusted public keys database.</b>  <b>Ability to configure the cryptographic functionality</b>  <b>Configure SSH:</b> &lt;45&gt;348: C9200-24T: Oct 18 2022 20:37:12: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh version 2 &lt;45&gt;349: C9200-24T: Oct 18 2022 20:37:27: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh server algorithm kex diffie-hellman-group14-sha1 &lt;45&gt;350: C9200-24T: Oct 18 2022 20:37:46: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh server algorithm encryption aes256-cbc aes128-cbc &lt;45&gt;351: C9200-24T: Oct 18 2022 20:38:03: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh server algorithm mac hmac-sha2-512 hmac-sha2-256 &lt;45&gt;352: C9200-24T: Oct 18 2022 20:38:19: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh server algorithm hostkey rsa-sha2-256 rsa-sha2-512 &lt;45&gt;318: C9200L-24T-4X: Oct 18 2022 22:28:17: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh server algorithm publickey rsa-sha2-256 rsa-sha2-512  <b>Configure IPsec:</b> &lt;189&gt;69: C9200-24T: Feb 2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:crypto ikev2 proposal syslogipsec &lt;189&gt;70: C9200-24T: Feb 2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:encryption aes-cbc-128 aes-cbc-256 &lt;189&gt;71: C9200-24T: Feb 2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:prf sha256 &lt;189&gt;72: C9200-24T: Feb 2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:integrity sha1 sha256 sha512 &lt;189&gt;73: C9200-24T: Feb 2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:group 14 &lt;189&gt;141: C9200-24T: Feb 2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:crypto ipsec security-association lifetime kilobytes 2560 </pre>
--	--	--

		<pre> &lt;189&gt;142: C9200-24T: Feb  2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:crypto ipsec security-association lifetime seconds 28800 &lt;189&gt;143: C9200-24T: Feb  2 2023 00:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:vty0 logged command:crypto ipsec transform-set SyslogTransform esp-aes 256 esp-sha256- hmac  <b><u>Ability to configure the thresholds for SSH rekeying</u></b> &lt;189&gt;680706: C9200-24T: Oct 20 2022 17:28:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh rekey time 10 &lt;189&gt;680707: C9200-24T: Oct 20 2022 17:28:59: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:ip ssh rekey volume 100  <b><u>Ability to set the time which is used for timestamps</u></b> See FPT_STM_EXT.1  <b><u>Reset Passwords</u></b> &lt;189&gt;11470: C9200-24T: Apr  6 2023 04:34:18: %PARSER-5- CFGLOG_LOGGEDCMD: User:TestUser5330 logged command:username TestUser5330 secret *  <b><u>Ability to configure the reference identifier for the peer</u></b> &lt;189&gt;447: C9200-24T: Feb 23 2023 07:29:20: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:crypto pki certificate map sanmap 1 &lt;189&gt;448: C9200-24T: Feb 23 2023 07:29:34: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:alt- subject-name eq tl16-16x.example.com  <b><u>Ability to manage the TOE's trust store and designate X509.v3 certificates as trust anchors</u></b> Create Trustpoint: &lt;189&gt;2209: C9200-24T: Apr 19 2023 02:19:54: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:crypto pki trustpoint rootca-rsa &lt;190&gt;2208: C9200-24T: Apr 19 2023 02:19:54: %PKI-6- TRUSTPOINT_CREATE: Trustpoint: rootca-rsa created succesfully  <b><u>Import CA Cert:</u></b> &lt;189&gt;2296: C9200-24T: Apr 19 2023 02:23:26: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:crypto pki authenticate rootca-rsa &lt;191&gt;2286: C9200-24T: Apr 19 2023 02:23:24: CRYPTO_PKI: trustpoint rootca-rsa authentication status = 0 &lt;191&gt;2287: C9200-24T: rootca-rsa:A CA certificate has been installed &lt;191&gt;2288: C9200-24T: #011#011#011Issuer-name : cn=rootca-rsa,e=rootca- rsa@gossamersec.com,o=GSS,l=Catonsville,st=MD,c=US &lt;191&gt;2289: C9200-24T: #011#011#011Subject-name : cn=rootca-rsa,e=rootca- rsa@gossamersec.com,o=GSS,l=Catonsville,st=MD,c=US </pre>
--	--	--

		<pre> &lt;191&gt;2290: C9200-24T: #011#011#011Serial-number: 010001 &lt;191&gt;2291: C9200-24T: #011#011#011End-date      : 2024- 11-28T00:40:43Z  <b><u>Generate Certificate Request</u></b> &lt;189&gt;397: C9200-24T: Feb  1 2023 22:19:45: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:crypto pki enroll rootca-rsa  <b><u>Remove Trustpoint &amp; Certs</u></b> &lt;189&gt;1908: C9200-24T: Apr 19 2023 02:04:55: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:no crypto pki trustpoint rootca-rsa &lt;190&gt;1905: C9200-24T: Apr 19 2023 02:04:55: %PKI-6- TRUSTPOINT_DELETE: Trustpoint: rootca-rsa deleted succesfully  <b><u>Ability to manage the trusted public keys database</u></b> <b><u>Configure public key authentication:</u></b> &lt;189&gt;11943: C9200-24T: Apr 11 2023 02:25:23: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:ip ssh server algorithm authentication publickey &lt;189&gt;11944: C9200-24T: Apr 11 2023 02:25:35: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:ip ssh server algorithm publickey ssh-rsa  <b><u>Configure User with public key:</u></b> &lt;189&gt;11960: C9200-24T: Apr 11 2023 02:26:30: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:ip ssh pubkey-chain &lt;189&gt;11961: C9200-24T: Apr 11 2023 02:26:36: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:username testadmin &lt;189&gt;11962: C9200-24T: Apr 11 2023 02:26:40: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:key-string &lt;189&gt;11963: C9200-24T: Apr 11 2023 02:27:21: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQADW07sikGOBE0wbiSiqDO/niFb0 BaceZzExysqqpID+kmhpnIi53nw/o5U4bvZ7wZVkogM3lhKimnYKeIir m8uci4W7cVccn4gzVOxZgdfAU6k7fG3H7YWiHiMd8X6WQCyATvb91jhd lC8XnUtyTNhzuiYh30kYMpeCh4tD4N1TMLyIagLZyiV/N7qe51Tvnjbe xC/M/xY/kl+ISTGyaWP/B &lt;189&gt;11964: C9200-24T: Apr 11 2023 02:27:24: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:tb97nclRDv85p3sFN9uJ8PSfUi9SAZx5kNe0ujrPhv2mYaws bZCYPjRV71tphpGiPHMCxLZSg5WH1fTGaWlPMWet6g7rAppW8LrXBn+W QyzzICWAv8qxDOCNhmRGMsT root@t116-16x  <b><u>Remove public key and association with user:</u></b> &lt;189&gt;11924: C9200-24T: Apr 11 2023 02:24:49: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:ip ssh pubkey-chain &lt;189&gt;11925: C9200-24T: Apr 11 2023 02:24:57: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin  logged command:no username testadmin  <b><u>Ability to import X509v3 certificates to the TOE's trust store</u></b> </pre>
--	--	---

		<pre> <b>Import CSR Generated Certificate:</b> &lt;189&gt;2665: C9200-24T: Apr 19 2023 03:44:30: %PARSER-5- CFGLOG_LOGGEDCMD: User:admin logged command:crypto pki import rootca-rsa certificate &lt;191&gt;2659: C9200-24T: Apr 19 2023 03:44:30: CRYPTO_PKI:cert_record-&gt;serial_number: 0195 &lt;191&gt;2660: C9200-24T: Apr 19 2023 03:44:30: CRYPTO_PKI: pubkey_name : 0~1#0130#011#006#003U#004#006#023#002US1#0130#011#006#00 3U#004#010#014#002MD1#0240#022#006#003U#004#007#014#013C atonsville1#0140 &lt;191&gt;2661: C9200-24T: #006#003U#004 &lt;191&gt;2662: C9200-24T: #014#003GSS1)0'#006#011*&lt;86&gt;H&lt;86&gt;÷#015#001#011#001#026#0 32rootca- rsa@gossamersec.com1#0230#021#006#003U#004#003#014 &lt;191&gt;2663: C9200-24T: rootca-rsa &lt;191&gt;2735: C9200-24T: Apr 19 2023 06:19:08: crypto_ca_certificate: saved cert to nvram:rootca- rsa#195.cer [OK] &lt;191&gt;2736: C9200-24T: Apr 19 2023 06:19:08: crypto_ca_certificate: saved cert to nvram:rootca- rsa#1CA.cer [OK]rootca-rsa:unlocked trustpoint rootca- rsa, refcount is 0 </pre>
--	--	---

FMT_SMF.1/MACSEC	All administrative actions;	<p><b><u>Generate a PSK based CAK and install it in the device</u></b>  &lt;45&gt;444: C9200-24T: Jun 29 2023 20:25:05: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:key-string *</p> <p><b><u>Manage the Key Server to create, delete, and activate MKA participants [as specified in 802.1X, sections 9.13 and 9.16 (cf. MIB object ieee8021XKayMkaParticipantEntry) and section. 12.2 (cf. function createMKA())];</u></b></p> <p><b>Create/Activate:</b>  &lt;47&gt;689: C9200-24T: Jun 26 2023 14:22:03: MKA-EVENT: Created New CA 0xBD928CD8 Participant on interface GigabitEthernet1/0/3 with SCI 6C8B.D3F3.A783/000A for Peer MAC 6c8b.d3f3.a783.</p> <p><b>Delete:</b>  &lt;47&gt;3495: C9200-24T: Jun 26 2023 15:28:12: MKA-EVENT: Deleting MKA Session on interface GigabitEthernet1/0/3 &amp; Bring-Down-Dot1x is TRUE.</p> <p><b>Specify a lifetime of a CAK</b>  &lt;45&gt;5170: C9200-24T: Jun 23 2023 15:18:58: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:lifetime local 11:18:48 Jun 23 2023 duration 600</p> <p><b><u>Enable, disable, or delete a PSK based CAK using [CLI management commands]</u></b></p> <p><b>Enable:</b>  &lt;45&gt;444: C9200-24T: Jun 29 2023 20:25:05: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:key-string *</p> <p><b>Disable/Delete:</b>  &lt;45&gt;446: C9200-24T: Jun 29 2023 20:25:07: %PARSER-5-CFGLOG_LOGGEDCMD: User:admin logged command:no key-string</p>
FPT_RPL.1	Detected replay attempt	<p>Detected replay attempt  &lt;47&gt;7391: C9200-24T: Jun 23 2023 16:51:19: MKA-ERR 0015.5d90.160e/0001 0000000D: MKPDU Validation FAIL - Live Peer MN 8 is NOT greater than last received MN 15 and so could be an old/replayed MKPDU.</p>
FPT_STM_EXT.1	Discontinuous changes to time - either Administrator actuated or changed via an automated process.	<p>&lt;190&gt;12072: C9200-24T: Apr 11 2023 06:37:47: %HA_EM-6-LOG: cli_log: User:admin via Port:0 Executed[clock set 10:25:20 15 April 2023]  &lt;190&gt;12073: C9200-24T: Apr 15 2023 15:25:20: %SYS-6-CLOCKUPDATE: System clock has been updated from 01:37:47 EST Tue Apr 11 2023 to 10:25:20 EST Sat Apr 15 2023, configured from console by admin on console.</p>

FPT_TUD_EXT.1	Initiation of update. result of the update attempt (success or failure)	<p><b>Success:</b></p> <pre>&lt;46&gt;505: C9200L-24T-4X: May 20 2023 01:21:57: %HA_EM-6-LOG: cli_log: User:admin via Port:0 Executed[install add file activate commit ] &lt;45&gt;506: C9200L-24T-4X: May 20 2023 01:22:04: %INSTALL-5-INSTALL_START_INFO: Switch 1 R0/0: install_engine: Started install one-shot flash:cat9k_lite_iosxe.17.09.02.SPA.bin &lt;45&gt;525: C9200L-24T-4X: May 20 2023 01:35:57: %INSTALL-5-INSTALL_COMPLETED_INFO: Switch 1 R0/0: install_engine: Completed install one-shot PACKAGE flash:cat9k_lite_iosxe.17.09.02.SPA.bin</pre> <p><b>Failure:</b></p> <pre>&lt;46&gt;489: C9200L-24T-4X: May 17 2023 22:46:52: %HA_EM-6-LOG: cli_log: User:admin via Port:0 Executed[install add file activate commit ] &lt;45&gt;490: C9200L-24T-4X: May 17 2023 22:46:59: %INSTALL-5-INSTALL_START_INFO: Switch 1 R0/0: install_engine: Started install one-shot flash:cat9k_lite_iosxe.17.09.02.SPA-modified_sig.bin &lt;43&gt;491: C9200L-24T-4X: May 17 2023 22:47:23: %INSTALL-3-OPERATION_ERROR_MESSAGE: Switch 1 R0/0: install_engine: Failed to install_add_activate_commit package flash:cat9k_lite_iosxe.17.09.02.SPA-modified_sig.bin, Error: File flash:cat9k_lite_iosxe.17.09.02.SPA-modified_sig.bin is corrupt or is not a valid package. &lt;43&gt;492: C9200L-24T-4X: May 17 2023 22:47:23: %INSTALL-3-OPERATION_ERROR_MESSAGE: Switch 1 R0/0: install_engine: Failed to install_add_activate_commit package flash:cat9k_lite_iosxe.17.09.02.SPA-modified_sig.bin, Error: install_add_activate_commit : flash:cat9k_lite_iosxe.17.09.02.SPA-modified_sig.bin is not valid file or cannot be handled by install CLI.</pre>
FTA_SSL_EXT.1	The termination of a local session by the session locking mechanism.	<pre>&lt;190&gt;925: C9200-24T: Mar 28 2023 19:22:00: %SYS-6-TTY_EXPIRE_TIMER: (exec timer expired, tty 0 (0.0.0.0)), user admin &lt;190&gt;926: C9200-24T: Mar 28 2023 19:22:00: %SYS-6-LOGOUT: User admin has exited tty session 0()</pre>
FTA_SSL.3	The termination of a remote session by the session locking mechanism.	<pre>&lt;190&gt;568: C9200-24T: Mar 28 2023 02:12:21: %SYS-6-TTY_EXPIRE_TIMER: (exec timer expired, tty 3 (172.16.16.254)), user admin &lt;190&gt;569: C9200-24T: Mar 28 2023 02:12:21: %SYS-6-LOGOUT: User admin has exited tty session 3(172.16.16.254) &lt;189&gt;570: C9200-24T: Mar 28 2023 02:12:21: %SSH-5-SSH2_CLOSE: SSH2 Session from 172.16.16.254 (tty = 1) for user 'admin' using crypto cipher 'aes256-cbc', hmac 'hmac-sha2-256' closed</pre>

FTA_SSL.4	The termination of an interactive session.	<p><b>SSH</b></p> <pre>&lt;190&gt;11096: C9200-24T: Apr 6 2023 04:14:13: %HA_EM-6-LOG: cli_log: User:TestUser5142 via Port:2 Executed[exit ] &lt;190&gt;11097: C9200-24T: Apr 6 2023 04:14:13: %SYS-6-LOGOUT: User TestUser5142 has exited tty session 2(172.16.16.254) &lt;189&gt;11098: C9200-24T: Apr 6 2023 04:14:13: %SSH-5-SSH2_CLOSE: SSH2 Session from 172.16.16.254 (tty = 0) for user 'TestUser5142' using crypto cipher 'aes256-cbc', hmac 'hmac-sha2-256' closed</pre> <p><b>Local Console</b></p> <pre>&lt;190&gt;1156: C9200-24T: Apr 13 2023 05:05:19: %HA_EM-6-LOG: cli_log: User:admin via Port:0 Executed[exit ] &lt;190&gt;1157: C9200-24T: Apr 13 2023 05:05:19: %SYS-6-LOGOUT: User admin has exited tty session 0()</pre>
FTP_ITC.1	Initiation of the IPsec trusted channel. Termination of the IPsec trusted channel. Failure of the IPsec trusted channel functions	<p><b>Initiation:</b></p> <pre>&lt;189&gt;29727: C9200-24T: Mar 10 2023 21:03:56: %IKEV2-5-SA_UP: SA UP &lt;189&gt;29728: C9200-24T: Mar 10 2023 21:03:56: %CRYPTO-5-IKEV2_SESSION_STATUS: Crypto tunnel v2 is UP. Peer 192.168.144.254:500 Id: 192.168.144.254 &lt;191&gt;29771: C9200-24T: Mar 10 2023 21:03:56: IKEv2:(SESSION ID = 7,SA ID = 1):(SA ID = 1):[IPsec -&gt;IKEv2] Creation of IPsec SA into IPsec database PASSED</pre> <p><b>Termination:</b></p> <pre>&lt;191&gt;7882: C9200-24T: Nov 8 2022 19:20:07: IKEv2:(SESSION ID = 29,SA ID = 1):Deleting SA &lt;189&gt;7883: C9200-24T: Nov 8 2022 19:20:07: %IKEV2-5-SA_DOWN: SA DOWN &lt;189&gt;7884: C9200-24T: Nov 8 2022 19:20:07: %CRYPTO-5-IKEV2_SESSION_STATUS: Crypto tunnel v2 is DOWN. Peer 192.168.144.254:4500 Id: 192.168.144.254</pre> <p>See FCS_IPSEC_EXT.1 for Audits associated with failures of IPsec Sessions.</p>
FTP_ITC.1/MACSEC	Initiation of the MACsec trusted channel. Termination of the MACsec trusted channel. Failure of the MACsec trusted channel functions	<p><b>Initiation:</b></p> <pre>&lt;47&gt;694: C9200-24T: Jun 26 2023 14:22:03: MKA-EVENT 6c8b.d3f3.a783/0000 0000000E: &gt;&gt; FSM - Initializing MKA Session for PSK keychain on interface GigabitEthernet1/0/3 with SCI 6C8B.D3F3.A783/000A.</pre> <p><b>Termination:</b></p> <pre>&lt;45&gt;3413: C9200-24T: Jun 26 2023 15:28:02: %MKA-5-SESSION_STOP: (Gi1/0/1 : 8) MKA Session stopped by MKA for RxSCI 0015.5d90.160e/0001, AuditSessionID , CKN 1000</pre> <p><b>Failure:</b></p> <pre>&lt;43&gt;7026: C9200-24T: Jun 23 2023 16:26:53: %MKA-3-MKPDU_VALIDATE_FAILURE: (Gi1/0/1 : 8) Validation of a MKPDU failed for RxSCI 0015.5d90.160e/0001, AuditSessionID , CKN 1000</pre>

FTP_TRP.1/Admin	Initiation of the SSH trusted path. Termination of the SSH trusted path. Failure of the SSH trusted path functions.	See FIA_UIA_EXT.1 for Audits of successful establishment of SSH sessions.  See FTA_SSL.3 and FTA_SSL.4.  See FCS_SSHS_EXT.1 for Audits associated with failures of SSH Sessions
FCS_MACSEC_EXT.1	Session establishment; Secure Channel Identifier (SCI)	Session Establishment <45>810: C9200-24T: Jun 26 2023 14:24:39: %MKA-5-SESSION_SECURED: (Gi1/0/1 : 8) MKA Session was secured for RxSCI 0015.5d90.160e/0001, AuditSessionID , CKN 1000
FCS_MACSEC_EXT.3	Creation and update of Secure Association Key; Creation and update times	<b><u>SAK (Security Association Key) creation</u></b> <46>2483: C9200-24T: Jun 26 2023 15:10:40: %MKA-6-SAK_REKEY: (Gi1/0/1 : 8) MKA Session is beginning a SAK Rekey (current Latest AN/KN 1/14, Old AN/KN 0/13) for RxSCI 0015.5d90.160e/0001, AuditSessionID , CKN 1000  <b><u>SAK (Security Association Key) update</u></b> <46>2506: C9200-24T: Jun 26 2023 15:10:41: %MKA-6-SAK_REKEY_SUCCESS: (Gi1/0/1 : 8) MKA Session successfully completed a SAK Rekey (new Latest AN/KN 2/15, Old AN/KN 1/14) for RxSCI 0015.5d90.160e/0001, AuditSessionID , CKN 1000
FCS_MACSEC_EXT.4	Creation of Connectivity Association; Connectivity Association Key Names	Creation of Connectivity Association <45>810: C9200-24T: Jun 26 2023 14:24:39: %MKA-5-SESSION_SECURED: (Gi1/0/1 : 8) MKA Session was secured for RxSCI 0015.5d90.160e/0001, AuditSessionID , CKN 1000

## 7. Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, see [What's New in Cisco Product Documentation](#).

To receive new and revised Cisco technical content directly to your desktop, you can subscribe to the [What's New in Cisco Product Documentation RSS feed](#). The RSS feeds are a free service.

## 8. Contacting Cisco

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).